

Loom & Tubing Accessories (Clamps, Clips)

Rubber Insulated Steel Clamps

- Provides electrical insulation, vibration absorption, and protection of wire & cable, hydraulic hoses and loom from abrasion & shock
- Holds lines firmly in place
- Standard-Grade Stainless Steel for longer life

- Insulation:** Black Silicone Rubber is very flexible and provides superior heat resistance. Temperature range: -55°C to +300°C (-67°F to 572°F)
- Contact Techspan if you require other sizes



Metal Width: 1/2" (12.7mm); Hole Diameter: 1/4"

ID Size	Actual Mounting Hole Diameter	Metal Thickness	10 PCS/PK	100 PCS/PK	500 PCS/PK
1/4" (6.4mm)	.268" (6.80mm)	0.8mm	766321	766321C	766321B
3/8" (9.5mm)	.268" (6.80mm)	0.8mm	766322	766322C	766322B
1/2" (12.7mm)	.268" (6.80mm)	0.8mm	766323	766323C	766323B
5/8" (15.9mm)	.268" (6.80mm)	0.8mm	766324	766324C	766324B
3/4" (19.1mm)	.268" (6.80mm)	0.8mm	766325	766325C	766325B
7/8" (22.2mm)	.268" (6.80mm)	0.8mm	766326	766326C	766326B
1" (25.4mm)	.268" (6.80mm)	0.8mm	766327	766327C	766327B
1-1/8" (28.6mm)	.268" (6.80mm)	0.8mm	766328	766328C	766328B
1-1/4" (31.8mm)	.268" (6.80mm)	0.8mm	766329	*766329C	766329B
1-1/2" (38.1mm)	.268" (6.80mm)	0.8mm	*766347	*766347C	
2" (50.8mm)	.268" (6.80mm)	0.8mm	*766348	*766348C	
3" (76.2mm)	.268" (6.80mm)	0.8mm	*766346	*766346C	



D

*NEW
*NEW
*NEW
*NEW

Metal Width: 5/8" (15.9mm); Hole Diameter: 3/8"

ID Size	Actual Mounting Hole Diameter	Metal Thickness	10 PCS/PK	100 PCS/PK	500 PCS/PK
1/4" (6.4mm)	.404" (10.25mm)	0.8mm	766330	*766330C	766330B
3/8" (9.5mm)	.404" (10.25mm)	0.8mm	766331	*766331C	766331B
1/2" (12.7mm)	.404" (10.25mm)	0.8mm	766332	*766332C	766332B
5/8" (15.9mm)	.404" (10.25mm)	0.8mm	766333	*766333C	766333B
3/4" (19.1mm)	.404" (10.25mm)	0.8mm	766334	*766334C	766334B
7/8" (22.2mm)	.404" (10.25mm)	0.8mm	766335	*766335C	766335B
1" (25.4mm)	.404" (10.25mm)	0.8mm	766336	*766336C	766336B
1-1/8" (28.6mm)	.404" (10.25mm)	0.8mm	766337	*766337C	766337B
1-1/4" (31.8mm)	.404" (10.25mm)	0.8mm	766338	*766338C	766338B
1-1/2" (38.1mm)	.404" (10.25mm)	0.8mm	766339	*766339C	766339B
2" (50.8mm)	.404" (10.25mm)	0.8mm	766340	766340C	
2-1/2" (63.5mm)	.404" (10.25mm)	0.8mm	766341	766341C	
3" (76.2mm)	.404" (10.25mm)	0.8mm	766342	766342C	



Rubber Insulated Steel Clamps

*NEW
*NEW
*NEW
*NEW
*NEW
*NEW
*NEW
*NEW
*NEW
*NEW

Rubber Insulated Stainless Steel Clamps

- Provides electrical insulation, vibration absorption, and protection of wire & cable, hydraulic hoses and loom from abrasion & shock
- Holds lines firmly in place
- 304-Grade Stainless Steel will not rust or corrode

- Insulation:** Black Silicone Rubber is very flexible and provides superior heat resistance. Temperature range: -55°C to +300°C (-67°F to 572°F)
- Contact Techspan if you require other sizes



Metal Width: 1/2" (12.7mm); Hole Diameter: 1/4"

ID Size	Actual Mounting Hole Diameter	Metal Thickness	10 PCS/PK	100 PCS/PK
1/4" (6.4mm)	.268" (6.8mm)	0.8mm	*766351	*766351C
3/8" (9.5mm)	.268" (6.8mm)	0.8mm	*766352	*766352C
1/2" (12.7mm)	.268" (6.8mm)	0.8mm	*766353	*766353C
5/8" (15.9mm)	.268" (6.8mm)	0.8mm	*766354	*766354C
3/4" (19.1mm)	.268" (6.8mm)	0.8mm	*766355	*766355C
7/8" (22.2mm)	.268" (6.8mm)	0.8mm	*766356	*766356C
1" (25.4mm)	.268" (6.8mm)	0.8mm	*766357	*766357C
1-1/4" (31.8mm)	.268" (6.8mm)	0.8mm	*766368	*766368C
1-1/2" (38.1mm)	.268" (6.8mm)	0.8mm	*766369	*766369C
2" (50.8mm)	.268" (6.8mm)	1.0mm	*766370	*766370C



Rubber Insulated Stainless Steel Clamps

*NEW
*NEW
*NEW
*NEW
*NEW
*NEW
*NEW
*NEW
*NEW
*NEW