



- ▶ Excellent colour rendering
- ▶ High system efficiency
- ▶ Compatible with all T8 electronic ballasts
- ▶ Energy savings and reduced maintenance cost
- ▶ Low mercury content and TCLP compliant
- ▶ One System extended lamp/ballast warranty
- ▶ XL31 lamps are ideal for applications where a high lumen rating is necessary
- ▶ Long life lamps are ideal for applications where relamping is a challenge



T8 Lamps

Order code	Description	Watts (W)	Base	Colour temp. (K)	CRI	Rated life IS (3 hrs)	Rated life IS (12 hrs)	Rated life PS/PRS (3 hrs)	Rated life PS/PRS (12 hrs)	Initial lumens (lm)	Mean lumens (lm)	Nominal length in. (mm)	Efficacy (lm/W)	Case qty
------------	-------------	-----------	------	------------------	-----	-----------------------	------------------------	---------------------------	----------------------------	---------------------	------------------	-------------------------	-----------------	----------

800 series ¹

Dia. : 1 in. (26 mm)

10014	F17T8/30K/8/RS/G13/STD ESV	17	G13*	3 000	85	N/A	N/A	24 000	30 000	1 400	1 330	24 (610)	82	25
10015	F17T8/35K/8/RS/G13/STD ESV	17	G13	3 500	85	N/A	N/A	24 000	30 000	1 400	1 330	24 (610)	82	25
10002	F17T8/41K/8/RS/G13/STD ESV	17	G13	4 100	85	N/A	N/A	24 000	30 000	1 400	1 330	24 (610)	82	25
10016	F25T8/30K/8/RS/G13/STD ESV	25	G13	3 000	85	24 000	30 000	30 000	36 000	2 150	2 040	36 (915)	86	25
10912	F25T8/35K/8/RS/G13/STD ESV	25	G13	3 500	85	24 000	30 000	30 000	36 000	2 150	2 040	36 (915)	86	25
10003	F25T8/41K/8/RS/G13/STD ESV	25	G13	4 100	85	24 000	30 000	30 000	36 000	2 150	2 040	36 (915)	86	25
58635	F25T8/830HL/ES/STD	25	G13	3 000	85	24 000	30 000	40 000	42 000	2 400	2 300	48 (1 220)	96	25
57124	F25T8/835HL/ES/STD	25	G13	3 500	85	24 000	30 000	40 000	42 000	2 400	2 300	48 (1 220)	96	25
57122	F25T8/841HL/ES/STD	25	G13	4 100	85	24 000	30 000	40 000	42 000	2 400	2 300	48 (1 220)	96	25
56505	F28T8/830HL/ES/STD	28	G13	3 000	85	24 000	30 000	40 000	42 000	2 725	2 560	48 (1 220)	97	25
56506	F28T8/835HL/ES/STD	28	G13	3 500	85	24 000	30 000	40 000	42 000	2 725	2 560	48 (1 220)	97	25
56507	F28T8/841HL/ES/STD	28	G13	4 100	85	24 000	30 000	40 000	42 000	2 725	2 560	48 (1 220)	97	25
56508	F28T8/850HL/ES/STD	28	G13	5 000	85	24 000	30 000	40 000	42 000	2 625	2 500	48 (1 220)	94	25
56501	F30T8/830HL/ES/STD	30	G13	3 000	86	24 000	30 000	40 000	42 000	2 850	2 700	48 (1 220)	95	25
56502	F30T8/835HL/ES/STD	30	G13	3 500	86	24 000	30 000	40 000	42 000	2 850	2 700	48 (1 220)	95	25
56503	F30T8/841HL/ES/STD	30	G13	4 100	86	24 000	30 000	40 000	42 000	2 850	2 700	48 (1 220)	95	25
56504	F30T8/850HL/ES/STD	30	G13	5 000	86	24 000	30 000	40 000	42 000	2 750	2 600	48 (1 220)	92	25
62981	F32T8/30K/8/RS/G13/STD ESV BULK	32	G13	3 000	85	24 000	30 000	40 000	42 000	3 050	2 900	48 (1 220)	95	25
51167	F32T8/35K/8/RS/G13/STD ESV	32	G13	3 500	85	24 000	30 000	40 000	42 000	3 050	2 900	48 (1 220)	95	25
51168	F32T8/41K/8/RS/G13/STD ESV	32	G13	4 100	85	24 000	30 000	40 000	42 000	3 050	2 900	48 (1 220)	92	25
59898	F32T8/41K/8/RS/G13/STD ESV BULK	32	G13	4 100	85	24 000	30 000	40 000	42 000	3 050	2 900	48 (1 220)	94	25
10004	F32T8/50K/8/RS/G13/STD ESV	32	G13	5 000	85	24 000	30 000	40 000	42 000	2 950	2 800	48 (1 220)	92	25
51170	F32T8/50K/9/RS/G13/STD ESV	32	G13	5 000	98	20 000	24 000	24 000	30 000	2 100	2 000	48 (1 220)	66	25
51174	F32T8/FS/RS/G13/STD	32	G13	5 700	92	20 000	24 000	24 000	30 000	2 300	2 185	48 (1 220)	72	25
62984	F32T8/65K/8/RS/G13/STD ESV BULK	32	G13	6 500	85	24 000	30 000	40 000	42 000	2 900	2 750	48 (1 220)	91	25
10309	F40T8/41K/8/RS/G13/STD	40	G13	4 100	85	20 000	24 000	24 000	30 000	3 700	3 600	60 (1 524)	93	25

T8 XL31 ¹

Dia. : 1 in. (26 mm)

10914	F32T8/830K/XL31/STD	32	G13	3 000	89	20 000	24 000	24 000	30 000	3 100	2 950	48 (1 220)	97	25
10915	F32T8/835K/XL31/STD	32	G13	3 500	89	20 000	24 000	24 000	30 000	3 100	2 950	48 (1 220)	97	25
10916	F32T8/841K/XL31/STD	32	G13	4 100	89	20 000	24 000	24 000	30 000	3 100	2 950	48 (1 220)	97	25
10917	F32T8/850K/XL31/STD	32	G13	5 000	89	20 000	24 000	24 000	30 000	3 000	2 850	48 (1 220)	94	25

T8 Long Life ²

Dia. : 1 in. (26 mm)

60855	F28T8/35K/8/RS/G13/STD ESV LL	28	G13	3 500	85	36 000	40 000	55 000	60 000	2 675	2 540	48 (1 220)	96	25
60854	F28T8/41K/8/RS/G13/STD ESV LL	28	G13	4 100	85	36 000	40 000	55 000	60 000	2 675	2 540	48 (1 220)	96	25
60857	F28T8/50K/8/RS/G13/STD ESV LL	28	G13	5 000	85	36 000	40 000	55 000	60 000	2 575	2 450	48 (1 220)	92	25
60853	F32T8/35K/8/RS/G13/STD ESV LL	32	G13	3 500	85	36 000	40 000	55 000	60 000	2 950	2 800	48 (1 220)	92	25
60852	F32T8/41K/8/RS/G13/STD ESV LL	32	G13	4 100	85	36 000	40 000	55 000	60 000	2 950	2 800	48 (1 220)	92	25
60856	F32T8/50K/8/RS/G13/STD ESV LL	32	G13	5 000	85	36 000	40 000	55 000	60 000	2 850	2 700	48 (1 220)	89	25

* G13 = Med Bipin

