



Overview

Lead time	Usually in Stock
-----------	------------------



General

Provided Equipment	Installation guide Safety guide
--------------------	------------------------------------

Physical

Color	Black
Depth	3.66 in (9.3 cm)
Height	9.45 in (24 cm)
Product Weight	2.01 lb(US) (0.91 kg)
Width	1.73 in (4.4 cm)

Input

Line Rated Current	12 A
Permissible voltage	100...240 V
Max line current	15 A
Input current limits	15 A
Load Capacity	2300 VA
Input Frequency	50/60 Hz
Plug standard	IEC 60320 C14
Nominal Input Voltage	100 V 120 V 200 V 208 V 230 V 240 V

Output

Number of power socket outlets	8 IEC 60320 C13
--------------------------------	-----------------

Conformance

Product Certifications	CUL Listed CE EAC IRAM UL Listed VDE
------------------------	---


Ordering and shipping details

GTIN	00731304327790
Package weight(Lbs)	3.02 lb(US) (1.37 kg)

Packing Units

Package 1 Height	11.26 in (28.6 cm)
Package 1 width	8.27 in (21 cm)
Package 1 Length	5.12 in (13 cm)
SCC14	10731304327797
Number of Units in Package 3	192

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Lead free	Yes
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------