



GE  
Lighting

94843 - null

#### F32T8SPX65ECO/CVG

- ☞ A shatter resistant lamp encased in a 0.015" Lexan® polycarbonate sleeve.
- ☞ Meets FDA food code 6-202 and 21CFR 110.20 regulations.
- ☞ Compliant with NSF/ANSI2 Standards for Food Equipment and UL2007A Shatter Containment of Lamps for Use in Regulated Food Establishments.
- ☞ Blocks UV lamp emissions up to 380nm.

#### Product Photo



#### GENERAL CHARACTERISTICS

Base Description	Medium Bi-pin
Base Type	Pin/Plug-in
Mercury Content	2.95 mg
Mercury-Picogram per mean lm hr	36.8
Rated Life Instant Start-Hrs	30000
Rated Life Rapid Start - Hrs	30000
Starting Temp (MIN) C-degrees	10 °C
Bulb Material	Soda lime
Product Technology	Linear Fluorescent
Base	G13
Bulb Shape	T8

#### PHOTOMETRIC CHARACTERISTICS

Mean Lumens nominal	2670 lm
Nominal Initial Lumen per Watt	87.5
Initial Lumens-nominal	2800 lm
Color Rendering Index-CRI	78
Color Temperature	6500 K

#### PRODUCT INFORMATION

Product Code	94843
Description	F32T8SPX65ECO/CVG
Alternative Unit Of Measure	EACH
Standard Package Quantity	36
Ean UPC	043168948432
Standard Package GTIN	00043168948432
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	36
Sales Unit	Each
UCC	043168948432
Alternative Unit Of Measure	CASE

#### DIMENSIONS

Diameter	1.0 in
Bulb Max Overall Length-MOL	48.0 in