



Actual

Catalog Number: LDXC6-272BLD
Product ID: 7TBA134580R0165
UPC Number: 62405009934
Status: A

Battery Unit, Voltage DC: 6V, Battery Wattage: 27W, two heads, Lamp Type: LED, 120VAC with linecord

- Compact 6 and 12 Volts Steel Battery Unit
- Fully automatic solid-state charger with test switch and AC-on pilot light
- Quick and easy installation, pre-assembled cordset, no batteries or board to remove before installation
- Universal Spider knockout pattern for junction box mounting
- Sealed dust-proof transfer relay circuit and low-voltage disconnect
- Long-life, maintenance-free lead acid battery
- NEXUS compatible

North American Specifications (UNSPSC)

UNSPSC	39111709 Emergency light unit
IGCC	3940 Emergency light unit
Brand Name	Ready-Lite
Type	Battery Units
Application	Institutional, Commercial
Standard	CSA
Wattage	27 W
Voltage Rating	120 VAC
Battery	Lead-calcium
Battery Runtime	30 minutes
Lamp Type	MR16 LED
Number Of Lamps	2
Size	9-1/8 Inches Height x 12-3/4 Inches Width
Material	Steel
Mounting	Universal
Color	Factory White
Lamp Wattage	4 W

European Specifications (ETIM)

ETIM	EC001957 Emergency luminaire
With lamp	Y
Material housing	Steel
Colour housing	White
Battery quality	Lead
Voltage type	AC/DC
Nominal voltage	120-120V
Width	308mm
Height/depth	232mm

Packaging

Outer Quantity	1
Outer Dimensions (inches)	1x1x1
Weight Uom	7 lbs. Each

Documents / Support Tools

Technical Drawing / Data Sheet Canada	Available on Website
Instruction Sheet Canada	Available on Website

For further technical assistance, please contact us...

ABB Installation Products Canada
700, Thomas Avenue
Saint-Jean-sur-Richelieu, QC
J2X 2M9
www.tnb.ca

ABB Installation Products Technical Support
<http://www.tnb.ca/en/contactus/?id=ALL>

Hours: 7h00 - 18h00
Monday-Friday