Safety switch, heavy duty, fused, viewing window, NEMA 12, 240V, 30A, 3 pole, neutral bonded, ground lugs



#### Main

Product	Single Throw Safety Switch
Duty Rating	Heavy duty
Device Application	Heavy application
Disconnect Type	Fusible disconnect
Factory Installed Neutral	Neutral (factory bonded)
Number of Poles	3
Current Rating	30 A
Voltage Rating	250 V DC 240 V AC
Enclosure Rating	NEMA 12 galvannealed steel
Motor power hp	1.5 Hp at 240 V AC 50-60 Hz for 1 phase motors 3 Hp at 240 V AC 50-60 Hz for 3 phase motors 3 Hp at 240 V AC 50-60 Hz for 1 phase motors 7.5 Hp at 240 V AC 50-60 Hz for 3 phase motors 5 hp at 250 V DC

Complementary

<u>Complementary</u>		
Short-circuit current	200 kA for J	
Fuse type	J	
Mounting Type	Surface	
Electrical Connection	Lugs	
Wiring configuration	4-wire (3PH + N)	
Wire Size	AWG 12AWG 6 aluminium AWG 14AWG 6 copper	
Tightening torque	45 Lbf.In (5.08 N.m) 0.02 in² (13.3 mm²) (AWG 6) 40 Lbf.In (4.52 N.m) 0.01 in² (8.367 mm²) (AWG 8) 35 lbf.in (3.95 N.m) 0.000.01 in² (2.065.261 mm²) (AWG 14AWG 10)	
Depth	5.195 in (131.95 mm)	
Width	6.48 in (164.59 mm)	
Height	14.57 in (370.08 mm)	
Net Weight	11.02 lb(US) (5 kg)	
Grounding Kit	Factory installation	
Service Entrance	Suitable service entrance for Canada	

#### Environment

Certifications	UL listed file E2875	

### Ordering and shipping details

Category	00113-H&HU SW,2&3P,N12,30-200A
Discount Schedule	DE1
GTIN	3606485893426
Returnability	Yes
Country of origin	US

# Packing Units

PCE
1
5.25 in (13.335 cm)
7.50 in (19.05 cm)
16.87 in (42.862 cm)
11.02 lb(US) (5 kg)

## Offer Sustainability

WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
Under investigation	
Product Environmental Profile	
No need of specific recycling operations	