LLL36000S40X

Automatic switch, PowerPact L, 400A, 3 pole, 600VAC, 50kA, lugs, magnetic





Main

Product or Component Type	Automatic switch
Range of Product	PowerPact L
Trip unit technology	Magnetic
Circuit breaker type	L-Frame

Complementary

Line Rated Current	400 A
[Ue] rated operational voltage	600 V AC
Mounting Mode	Unit mount
Poles description	3P
Short-circuit withstand	125 KA 240 V UL 489 100 KA 480 V UL 489 50 kA 600 V UL 489
Breaking capacity code	L
Electrical connection	Lugs, line Lugs, load
AWG gauge	X AWG 2/0500 kcmil (aluminium/copper)
Terminal identifier	AL600LS52K3
Magnetic tripping current	4800 A
Height	13.38 in (339.85 mm)
Width	5.51 in (139.95 mm)
Depth	6.61 in (167.89 mm)
Tightening torque	442.54 lbf.in (50 N.m) 0.110.37 in² (70240 mm²) (AWG 2/0500 kcmil)

Environment

Product Certifications	CSA[RETURN]IEC[RETURN]UL Listed	:

Ordering and shipping details

Category	01116-L ELEC TRIP UNIT MOUNT BREAKER/SW
Discount Schedule	DE2
GTIN	785901731689
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.75 in (22.225 cm)
Package 1 Width	10.75 in (27.305 cm)
Package 1 Length	19.50 in (49.53 cm)
Package 1 Weight	15.00 lb(US) (6.804 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	☐ China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	☑ End Of Life Information
PVC free	Yes

Contractual warranty

Somiastical warranty		
Warranty	18 months	