



## Main

|                                    |  |
|------------------------------------|--|
| Range of product                   | OsiSense XS  |
| Series name                        | General purpose                                    |
| Sensor type                        | Inductive proximity sensor                         |
| Sensor name                        | XS4  |
| Sensor design                      | Cylindrical M30                                    |
| Size                               | 62 mm  |
| Body type                          | Fixed  |
| Detector flush mounting acceptance | Non flush mountable                                |
| Material                           | Plastic  |
| Type of output signal              | Discrete   |
| Wiring technique                   | 3-wire   |
| [Sn] nominal sensing distance      | 15 mm  |
| Discrete output function           | 1 NO   |
| Output circuit type                | DC   |
| Discrete output type               | PNP  |
| Electrical connection              | Cable  |
| Cable length                       | 6.56 ft (2 m)                                      |
| [Us] rated supply voltage          | 12...48 V DC with reverse polarity protection      |
| Switching capacity in mA           | <= 200 mA DC overload and short-circuit protection |
| IP degree of protection            | IP68 double insulation conforming to IEC 60529     |

## Complementary

|                    |           |
|--------------------|-----------|
| Thread type        | M30 x 1.5 |
| Detection face     | Frontal   |
| Front material     | PPS       |
| Enclosure material | PPS       |

|                          |                              |
|--------------------------|------------------------------|
| Operating zone           | 0.00...0.47 in (0...12 mm)   |
| Differential travel      | 1...15% of Sr                |
| Cable composition        | 3 x 0.34 mm <sup>2</sup>     |
| Wire insulation material | PvR                          |
| Status LED               | Output state: 1 LED (yellow) |
| Supply voltage limits    | 10...58 V DC                 |
| Switching frequency      | <= 1000 Hz                   |
| Maximum voltage drop     | <2 V closed)                 |
| Current consumption      | 0...10 mA no-load            |
| Maximum delay first up   | 10 ms                        |
| Maximum delay response   | 0.3 ms                       |
| Maximum delay recovery   | 0.7 ms                       |
| Marking                  | CE                           |
| Threaded length          | 2.05 in (52 mm)              |
| Height                   | 1.18 in (30 mm)              |
| Length                   | 2.44 in (62 mm)              |

## Environment

|                                       |   |
|---------------------------------------|---|
| Product certifications                | UL<br>CSA<br>CCC<br>Ecolab              |
| Ambient air temperature for operation | -13...158 °F (-25...70 °C)              |
| Ambient air temperature for storage   | -40...185 °F (-40...85 °C)              |
| Vibration resistance                  | 25 gn +/- 2 mm 10...55 Hz)IEC 60068-2-6 |
| Shock resistance                      | 50 gn 11 ms IEC 60068-2-27              |

## Packing Units

|                              |                   |
|------------------------------|-------------------|
| Unit Type of Package 1       | PCE               |
| Number of Units in Package 1 | 1                 |
| Package 1 Weight             | 5.01 oz (141.9 g) |
| Package 1 Height             | 1.65 in (4.2 cm)  |
| Package 1 width              | 3.74 in (9.5 cm)  |
| Package 1 Length             | 5.20 in (13.2 cm) |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product   |
| REACH Regulation           | <a href="#">REACH Declaration</a>   |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope)<br><a href="#">EU RoHS Declaration</a> |
| Mercury free               | Yes   |
| RoHS exemption information | <a href="#">Yes</a>   |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>   |
| Circularity Profile        | <a href="#">End of Life Information</a>   |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|