

RSL1PVFU

slim interface relay, Harmony
Electromechanical Relays, pre assembled, 6A,
1CO, with LED, screw connec to rs, 110V AC/
DC



Main

| | |
|--|---|
| Range of Product | Harmony Electromechanical Relays |
| Series name | Interface relay |
| Product or Component Type | Pre-assembled plug-in relay with socket |
| Device short name | RSL |
| Contacts type and composition | 1 C/O |
| Contact operation | Standard |
| [Uc] control circuit voltage | 60 V DC |
| [Ithe] conventional enclosed thermal current | 6 A -40...131 °F (-40...55 °C) |
| Status LED | With |
| Shape of pin | Flat (PCB type) |

Complementary

| | |
|--|---|
| Fixing Mode | Plastic compression spring |
| Average resistance | 20500 Ohm DC 23 °C +/- 10 % |
| [Ui] rated insulation voltage | 250 V IEC 277 V cUL |
| [Uimp] rated impulse withstand voltage | 6 kV IEC |
| Contacts material | Silver alloy (AgSnO2) |
| [Ie] rated operational current | 6 A 1 C/O AC-1/DC-1)IEC/UL |
| Minimum switching current | 100 mA |
| Maximum switching voltage | 277 V |
| Minimum switching voltage | 12 V |
| Maximum switching capacity | 1500 VA 150 W |
| Minimum switching capacity | 120 mW |
| Operating rate | <= 72000 cycles/hour no-load <= 360 cycles/hour under load |
| Mechanical durability | 10000000 cycles |
| Electrical durability | 60000 cycles resistive, 6 A 250 V, AC-1 |
| Operating time | 5 ms reset 12 ms |
| Reset time | 20 ms |
| Marking | CE |
| Protection category | RT III |
| Test levels | Level A group mounting |
| Operating position | Any position |
| Height | 3.09 in (78.6 mm) |
| Width | 0.24 in (6.2 mm) |
| Depth | 3.74 in (95 mm) |
| Terminals description ISO n°1 | (A1-A2)CO (11-12-14)OC |
| Sale per indivisible quantity | 10 |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

| | |
|------------------------------|--|
| Net Weight | 0.06 lb(US) (0.029 kg) |
| Load current | 6 A 250 V AC 0.5 mm mounting distance |
| Average coil consumption | 0.17 W, DC |
| Drop-out voltage threshold | >= 0.05 Uc |
| Contact terminal arrangement | Separate |
| Connections - terminals | Screw connectors, 1 x 0.2...1 x 2.5 mm ² AWG 24...AWG 14) flexible with cable end Screw connectors, 1 x 0.2...1 x 2.5 mm ² AWG 24...AWG 14) solid without cable end |
| Tightening torque | < 0.5 N.m M2.5 |
| Safety reliability data | B10d = 60000 |
| Control type | Without push-button |
| Mounting Support | 35 mm symmetrical DIN rail |
| Device presentation | Complete product |

Environment

| | |
|---------------------------------------|--|
| Input voltage | 110 V AC/DC 88...126.5 V) |
| Dielectric strength | 1000 V AC between contacts 4000 V AC between coil and contact |
| Standards | CSA C22.2 No 14 IEC 61810-1 UL 508 |
| Product Certifications | CSA[RETURN]UL[RETURN]GOST |
| Ambient Air Temperature for Storage | -40...185 °F (-40...85 °C) |
| Vibration resistance | 10 gn +/- 1 mm 10...150 Hz)10 cycles not operating IEC 60068-2-6 5 gn +/- 1 mm 10...150 Hz)10 cycles in operation IEC 60068-2-6 |
| IP degree of protection | IP40 conforming to IEC 60529 |
| Shock resistance | 10 gn 11 ms) in operation IEC 60068-2-27 5 gn 11 ms) not operating IEC 60068-2-27 |
| Ambient air temperature for operation | -40...158 °F (-40...70 °C) |

Ordering and shipping details

| | |
|-------------------|-----------------------------|
| Category | 21127-ZELIO ICE CUBE RELAYS |
| Discount Schedule | CP2 |
| GTIN | 3606480077852 |
| Returnability | Yes |
| Country of origin | CN |

Packing Units

| | |
|------------------------------|-------------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 2.76 in (7.000 cm) |
| Package 1 Width | 3.39 in (8.600 cm) |
| Package 1 Length | 4.06 in (10.300 cm) |
| Package 1 Weight | 0.99 oz (28.000 g) |
| Unit Type of Package 2 | BB1 |
| Number of Units in Package 2 | 10 |
| Package 2 Height | 2.76 in (7.000 cm) |
| Package 2 Width | 3.39 in (8.600 cm) |
| Package 2 Length | 4.06 in (10.300 cm) |
| Package 2 Weight | 11.11 oz (315.000 g) |
| Unit Type of Package 3 | S03 |
| Number of Units in Package 3 | 300 |
| Package 3 Height | 11.81 in (30.000 cm) |
| Package 3 Width | 11.81 in (30.000 cm) |
| Package 3 Length | 15.75 in (40.000 cm) |
| Package 3 Weight | 21.96 lb(US) (9.960 kg) |

Offer Sustainability

| | |
|----------------------------|--|
| Sustainable offer status | Green Premium product |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End Of Life Information |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Dimensions

