


TECHNICAL INFORMATION BULLETIN

Pulse Start System Pulsetek™

Ordering Information

Order code: 68606
 Description: MH50W/U/UVS/PS STD
 UPC: 069549017740
 Case quantity: 12
 ANSI code: M110/O




Performance Data

Wattage (W):	50
Initial lumens (lm):	3 200
Mean lumens (lm):	2 100
Lumens per watt (lm/W):	77
Lamp voltage (V):	85
Colour temperature (K):	4 200
Chromaticity (x,y):	0.385, 0.390
CRI:	65
Average life (hrs):	10 000
Lamp lumen depreciation:	0.65% @ 4 000 hrs
Warm up time to 90% (min):	1-2
Hot restart time to 90% (min):	2-4
Burn Position:	Universal
Dimming:	50% rated power
Max base temperature:	190
Max lamp temperature:	400
Socket pulse rating (kV):	4



Spectral Distribution



Physical Data / Requirements

Shape:	EDX17
Base:	Med Base E26
Finish:	Clear
Luminaire rating:	Open Rated
Diameter (mm/in.):	56.0 (2 1/5)
MOL (mm/in.):	138.0 (5 7/16)
LCL (mm/in.):	86.0 (3 3/8)
Effective arc length (mm):	6.5
Mercury Content (mg):	9.5

Warning

“R” WARNING: THIS LAMP CAN CAUSE SERIOUS SKIN BURN AND EYE INFLAMMATION FROM SHORTWAVE ULTRAVIOLET RADIATION IF THE OUTER ENVELOPE OF THE LAMP IS BROKEN OR PUNCTURED. DO NOT USE WHERE PEOPLE WILL REMAIN FOR MORE THAN A FEW MINUTES UNLESS ADEQUATE SHIELDING OR OTHER SAFETY PRECAUTIONS ARE USED. LAMPS THAT WILL AUTOMATICALLY EXTINGUISH WHEN THE OUTER ENVELOPE IS BROKEN OR PUNCTURED ARE COMMERCIALY AVAILABLE. Complies with USA Federal Standard 21 CFR 1040.30 and Canada Standard C.R.C., c. 1370.