


**H10,0/24D ZH R****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

- supplied loose in poly-bag
- Weidmüller colour code
- DIN colour code
- other colour code

**General ordering data**

|            |                                                            |
|------------|------------------------------------------------------------|
| Version    | Wire-end ferrule, Twin wire-end ferrule, 17 mm, 12 mm, red |
| Order No.  | <a href="#">9037570000</a>                                 |
| Type       | H10,0/24D ZH R                                             |
| GTIN (EAN) | 4008190493141                                              |
| Qty.       | 100 pc(s).                                                 |
| Packaging  | loose                                                      |

## H10,0/24D ZH R

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|            |       |
|------------|-------|
| Net weight | 0.8 g |
|------------|-------|

## Technical data

|                        |                            |         |                       |
|------------------------|----------------------------|---------|-----------------------|
| Description of article | Twin wire end ferrule, red | Version | Twin wire-end ferrule |
|------------------------|----------------------------|---------|-----------------------|

## Wire-end ferrules

|                                         |         |                             |                    |
|-----------------------------------------|---------|-----------------------------|--------------------|
| Collar height (A)                       | 13.4 mm | Collar width (B)            | 7.6 mm             |
| Colour code                             | DIN     | Conductor cross-section     | 10 mm <sup>2</sup> |
| Contact surface diameter (D1)           | 5.8 mm  | Contact surface length (L2) | 12 mm              |
| L1 in mm                                | 24 mm   | Metal sleeve thickness (S1) | 0.2 mm             |
| Plastic collar thickness (S2)           | 0.5 mm  | Stripping length            | 17 mm              |
| Wire connection cross section AWG, max. | AWG 8   |                             |                    |

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000005    | ETIM 7.0    | EC000005    |
| ETIM 8.0    | EC000005    | ETIM 9.0    | EC000005    |
| ECLASS 9.0  | 27-40-02-01 | ECLASS 9.1  | 27-40-02-01 |
| ECLASS 10.0 | 27-40-02-01 | ECLASS 11.0 | 27-40-02-01 |
| ECLASS 12.0 | 27-40-02-01 | ECLASS 13.0 | 27-40-02-01 |
| ECLASS 14.0 | 27-40-02-01 |             |             |

## Environmental Product Compliance

|                        |                             |
|------------------------|-----------------------------|
| RoHS Compliance Status | Compliant without exemption |
| REACH SVHC             | No SVHC above 0.1 wt%       |

## Approvals

Approvals



|                         |            |
|-------------------------|------------|
| ROHS                    | Conform    |
| UL File Number Search   | UL Website |
| Certificate no. (cULus) | E499744    |

## Downloads

|                    |                                                                                          |
|--------------------|------------------------------------------------------------------------------------------|
| Engineering Data   | <a href="#">CAD data – STEP</a>                                                          |
| User Documentation | <a href="#">Technical information - EN</a><br><a href="#">Technical information - DE</a> |
| Catalogues         | <a href="#">Catalogues in PDF-format</a>                                                 |
| Brochures          |                                                                                          |

**H10,0/24D ZH R****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Drawings****Drawing**