


BSH0702T12F1A

AC servo motor BSH - 2.12 N.m - 6000 rpm -
keyed shaft - with brake - IP50



Main

Product or component type	Servo motor
Device short name	BSH
Maximum mechanical speed	8000 rpm
Continuous stall torque	19.47 Lbf.In (2.2 N.m) LXM32.D30M2 10 A, 115 V, single phase 18.76 Lbf.In (2.12 N.m) LXM05AD17M2, 200...240 V, single phase 18.76 Lbf.In (2.12 N.m) LXM05BD17M2, 200...240 V, single phase 18.76 Lbf.In (2.12 N.m) LXM05CD17M2, 200...240 V, single phase 19.47 Lbf.In (2.2 N.m) LXM32.D18M2 6 A, 230 V, single phase 18.76 Lbf.In (2.12 N.m) LXM05AD17F1, 110...120 V, single phase 18.76 Lbf.In (2.12 N.m) LXM05AD28M2, 200...240 V, single phase 18.76 Lbf.In (2.12 N.m) LXM05BD17F1, 110...120 V, single phase 18.76 Lbf.In (2.12 N.m) LXM05BD28M2, 200...240 V, single phase 18.76 Lbf.In (2.12 N.m) LXM05CD17F1, 110...120 V, single phase 18.76 Lbf.In (2.12 N.m) LXM05CD28M2, 200...240 V, single phase 18.76 Lbf.In (2.12 N.m) LXM15LD17N4, 230 V, three phase 18.76 Lbf.In (2.12 N.m) LXM15LD21M3, 230 V, three phase 18.76 Lbf.In (2.12 N.m) LXM05AD42M3X, 200...240 V, three phase 18.76 Lbf.In (2.12 N.m) LXM05BD42M3X, 200...240 V, three phase 18.76 lbf.in (2.12 N.m) LXM05CD42M3X, 200...240 V, three phase
Peak stall torque	53.99 Lbf.In (6.1 N.m) LXM32.D30M2 10 A, 115 V, single phase 63.73 Lbf.In (7.2 N.m) LXM32.D18M2 6 A, 230 V, single phase 36.64 Lbf.In (4.14 N.m) LXM05AD17F1, 110...120 V, single phase 36.64 Lbf.In (4.14 N.m) LXM05AD17M2, 200...240 V, single phase 36.64 Lbf.In (4.14 N.m) LXM05BD17F1, 110...120 V, single phase 36.64 Lbf.In (4.14 N.m) LXM05BD17M2, 200...240 V, single phase 36.64 Lbf.In (4.14 N.m) LXM05CD17F1, 110...120 V, single phase 36.64 Lbf.In (4.14 N.m) LXM05CD17M2, 200...240 V, single phase 60.18 Lbf.In (6.8 N.m) LXM05AD28M2, 200...240 V, single phase 60.18 Lbf.In (6.8 N.m) LXM05BD28M2, 200...240 V, single phase 60.18 Lbf.In (6.8 N.m) LXM05CD28M2, 200...240 V, single phase 39.56 Lbf.In (4.47 N.m) LXM15LD17N4, 230 V, three phase 48.24 Lbf.In (5.45 N.m) LXM15LD21M3, 230 V, three phase 60.18 Lbf.In (6.8 N.m) LXM05AD42M3X, 200...240 V, three phase 60.18 Lbf.In (6.8 N.m) LXM05BD42M3X, 200...240 V, three phase 60.18 lbf.in (6.8 N.m) LXM05CD42M3X, 200...240 V, three phase

Nominal output power	550 W LXM32.D30M2 10 A, 115 V, single phase 600 W LXM05AD17M2, 200...240 V, single phase 600 W LXM05BD17M2, 200...240 V, single phase 600 W LXM05CD17M2, 200...240 V, single phase 570 W LXM05AD17F1, 110...120 V, single phase 570 W LXM05BD17F1, 110...120 V, single phase 570 W LXM05CD17F1, 110...120 V, single phase 600 W LXM05AD28M2, 200...240 V, single phase 600 W LXM05BD28M2, 200...240 V, single phase 600 W LXM05CD28M2, 200...240 V, single phase 950 W LXM32.D18M2 6 A, 230 V, single phase 1000 W LXM15LD17N4, 230 V, three phase 1000 W LXM15LD21M3, 230 V, three phase 600 W LXM05AD42M3X, 200...240 V, three phase 600 W LXM05BD42M3X, 200...240 V, three phase 600 W LXM05CD42M3X, 200...240 V, three phase
Nominal torque	18.32 Lbf.In (2.07 N.m) LXM32.D30M2 10 A, 115 V, single phase 16.82 Lbf.In (1.9 N.m) LXM05AD17M2, 200...240 V, single phase 16.82 Lbf.In (1.9 N.m) LXM05BD17M2, 200...240 V, single phase 16.82 Lbf.In (1.9 N.m) LXM05CD17M2, 200...240 V, single phase 16.20 Lbf.In (1.83 N.m) LXM05AD17F1, 110...120 V, single phase 16.20 Lbf.In (1.83 N.m) LXM05BD17F1, 110...120 V, single phase 16.20 Lbf.In (1.83 N.m) LXM05CD17F1, 110...120 V, single phase 16.82 Lbf.In (1.9 N.m) LXM05AD28M2, 200...240 V, single phase 16.82 Lbf.In (1.9 N.m) LXM05BD28M2, 200...240 V, single phase 16.82 Lbf.In (1.9 N.m) LXM05CD28M2, 200...240 V, single phase 15.93 Lbf.In (1.8 N.m) LXM32.D18M2 6 A, 230 V, single phase 14.69 Lbf.In (1.66 N.m) LXM15LD17N4, 230 V, three phase 14.69 Lbf.In (1.66 N.m) LXM15LD21M3, 230 V, three phase 16.82 Lbf.In (1.9 N.m) LXM05AD42M3X, 200...240 V, three phase 16.82 Lbf.In (1.9 N.m) LXM05BD42M3X, 200...240 V, three phase 16.82 lbf.in (1.9 N.m) LXM05CD42M3X, 200...240 V, three phase
Nominal speed	2500 rpm LXM32.D30M2 10 A, 115 V, single phase 3000 rpm LXM05AD17F1, 110...120 V, single phase 3000 rpm LXM05BD17F1, 110...120 V, single phase 3000 rpm LXM05CD17F1, 110...120 V, single phase 3000 rpm LXM05AD17M2, 200...240 V, single phase 3000 rpm LXM05BD17M2, 200...240 V, single phase 3000 rpm LXM05CD17M2, 200...240 V, single phase 3000 rpm LXM05AD28M2, 200...240 V, single phase 3000 rpm LXM05BD28M2, 200...240 V, single phase 3000 rpm LXM05CD28M2, 200...240 V, single phase 5000 rpm LXM32.D18M2 6 A, 230 V, single phase 3000 rpm LXM05AD42M3X, 200...240 V, three phase 3000 rpm LXM05BD42M3X, 200...240 V, three phase 3000 rpm LXM05CD42M3X, 200...240 V, three phase 6000 rpm LXM15LD17N4, 230 V, three phase 6000 rpm LXM15LD21M3, 230 V, three phase

Product compatibility	LXM05AD17F1 110...120 V single phase LXM05AD17M2 200...240 V single phase LXM05AD28M2 200...240 V single phase LXM05BD17F1 110...120 V single phase LXM05BD17M2 200...240 V single phase LXM05BD28M2 200...240 V single phase LXM05CD17F1 110...120 V single phase LXM05CD17M2 200...240 V single phase LXM05CD28M2 200...240 V single phase LXM32.D30M2 115 V single phase LXM32.D18M2 230 V single phase LXM15LD21M3 230 V three phase LXM05AD42M3X 200...240 V three phase LXM05BD42M3X 200...240 V three phase LXM05CD42M3X 200...240 V three phase LXM15LD17N4 230 V three phase
Shaft end	Keyed
IP degree of protection	IP50 standard
Speed feedback resolution	131072 points/turn x 4096 turns
Holding brake	With
Mounting support	International standard flange
Electrical connection	Straight connectors

Complementary

Range compatibility	Lexium 05 Lexium 15 Lexium 32
Supply voltage max	480 V
Phase	Three phase
Continuous stall current	4.9 A
Maximum continuous power	1.51 W
Maximum current Irms	20.6 A LXM15LD21M3 20.6 A LXM15LD17N4 19.9 A LXM05AD17F1 19.9 A LXM05AD17M2 19.9 A LXM05AD28M2 19.9 A LXM05AD42M3X 19.9 A LXM05BD17F1 19.9 A LXM05BD17M2 19.9 A LXM05BD28M2 19.9 A LXM05BD42M3X 19.9 A LXM05CD17F1 19.9 A LXM05CD17M2 19.9 A LXM05CD28M2 19.9 A LXM05CD42M3X 15 A LXM32.D30M2 18 A LXM32.D18M2
Maximum permanent current	19.9 A
Switching frequency	8 kHz
Second shaft	Without second shaft end
Shaft diameter	0.43 in (11 mm)
Shaft length	0.91 in (23 mm)
Key width	0.71 in (18 mm)
Feedback type	Multiturn SinCos Hiperface
Holding torque	17.70 lbf.in (2 N.m) holding brake
Motor flange size	2.76 in (70 mm)
Number of motor stacks	2
Torque constant	0.45 N.m/A 248 °F (120 °C)
Back emf constant	28 V/krpm 248 °F (120 °C)
Number of motor poles	6
Rotor inertia	0.482 kg.cm²
Stator resistance	1.5 Ohm 68 °F (20 °C)
Stator inductance	6.7 mH 68 °F (20 °C)
Stator electrical time constant	4.47 ms 68 °F (20 °C)

Maximum radial force Fr	390 N 6000 rpm 410 N 5000 rpm 450 N 4000 rpm 490 N 3000 rpm 560 N 2000 rpm 710 N 1000 rpm
Maximum axial force Fa	0.2 x Fr
Brake pull-in power	10 W
Type of cooling	Natural convection
Length	8.37 in (212.5 mm)
Centring collar diameter	2.36 in (60 mm)
Centring collar depth	0.10 in (2.5 mm)
Number of mounting holes	4
Mounting holes diameter	0.22 in (5.5 mm)
Circle diameter of the mounting holes	3.23 in (82 mm)
Net weight	6.61 lb(US) (3 kg)

Ordering and shipping details

Category	18282 - LEXIUM 32 MOTORS
Discount Schedule	PC53
GTIN	03389118136625
Nbr. of units in pkg.	1
Package weight(Lbs)	7.2 lb(US) (3.27 kg)
Returnability	No
Country of origin	DE

Packing Units


Unit Type of Package 1	PCE
Package 1 Height	4.84 in (12.3 cm)
Package 1 width	5.04 in (12.8 cm)
Package 1 Length	14.84 in (37.7 cm)

Contractual warranty

Warranty	18 months
----------	-----------

Servo Motors Dimensions

Example with Straight Connectors



- a: Power supply for servo motor brake
b: Power supply for servo motor encoder
(1) M4 screw
(2) Shaft end, keyed slot (optional)

Dimensions in mm

Straight connectors		Rotatable angled connectors		c (without brake)	c (with brake)	c1	c2	c3	h	h1	Ø	Ø1 for screws
b1	b2	b1	b2									
39.5	25.5	39.5	39.5	187	213	23	18	2.5	4 N9	2.5 ^{+0.1} ₀	11 k6	M4 x 10


Dimensions in in.

Straight connectors		Rotatable angled connectors		c (without brake)	c (with brake)	c1	c2	c3	h	h1	Ø	Ø1 for screws
b1	b2	b1	b2									
1.55	1.00	1.55	1.55	7.36	8.38	0.90	0.70	0.09	0.16 N9	0.01 ^{+0.004} ₀	0.43 k6	M4 x 0.39

115 V Single-Phase Supply Voltage

Torque/Speed Curves

Servo motor with LXM32•D30M2 servo drive




- X Speed in rpm
Y Torque in Nm
1 Peak torque
2 Continuous torque

230 V Single-Phase Supply Voltage

Torque/Speed Curves

Servo motor with LXM32•D18M2 servo drive



- X Speed in rpm
Y Torque in Nm
1 Peak torque
2 Continuous torque