

Type	C4-A4x/ ... V Standard relays, 4 change-over contacts				
Maximum contact load	10 A/250 V	AC-1	0,5 A/110 V	DC-1	
	10 A/30 V	DC-1	0,2 A/220 V	DC-1	
Recommended minimum contact load	10 mA/10 V	Code 0, 9			
	5 mA/5 V	Code 8			
Contacts					
Material	Standard	Code 0	AgNi		
	Optional	Code 8	AgNi + 10 μ Au		
	Optional	Code 9	AgNi + 0,2 μ Au		
Rated current			10 A		
Switch-on current max. (20 ms)			30 A		
Switching voltage max.			250 V		
AC load (Fig 1)			2,5 kVA		
DC load			see Fig. 2		

Coil

Coil resistance	see table; tolerance ± 10 %
Pick-up voltage	≤ 0,8 × U _N
Release voltage	≥ 0,1 × U _N
Nominal power	2,4 VA (AC)/1,4 W (DC)

Coil table

VAC	Ω	mA	VDC	Ω	mA
24	65	100	24	414	58
48	286	50	48	1K6	30
115	1K7	21	110	8K1	13
230	6K8	10	220	35K7	6,2

Insulation

	Volt rms, 1 min
Contact open	1000 V
Contact/contact	2,5 kV
Contact/coil	2,5 kV
Insulation resistance at 500 V	≥ 1 GΩ
Insulation, IEC 61810-1	2,5 kV/3

Specifications

Ambient temperature operation/storage	-40 (no ice)...60 °C / -40 ... 80 °C
Pick-up time/bounce time	20 ms/≤ 3 ms
Release time/bounce time	8 ms/≤ 1 ms
Mechanical life ops	AC: 10 Mill./DC: 20 Mill.
DC voltage endurance at rated load	≥ 100000 switching cycles
Switching frequency at rated load	≤ 1200/ops/h
Protection class	IP40
Weight	90 g

Standard types

VAC 50 Hz/60 Hz: 24, 48, 115, (120), 230, (240)

LED

RC suppresor

VDC 24, 48, 110, 220

LED

Free wheeling diode

Polarity and free wheeling diode

AC/DC bridge rectifier 24 V, 48 V, 60 V

C4-A40/AC ... V

C4-A40X/AC ... V

C4-A40R/AC ... V

C4-A40/DC ... V

C4-A40X/DC ... V

C4-A40DX/DC ... V

C4-A40FX/DC ... V

C4-A40BX/UC ... V

C4-A48/AC ... V

C4-A48X/AC ... V

C4-A48R/AC ... V

C4-A48/DC ... V

C4-A48X/DC ... V

C4-A48DX/DC ... V

C4-A48FX/DC ... V

C4-A48BX/UC ... V

"..." Enter the voltage for full type designation





Accessories

Socket:

Optional accessories (blanking plug):

S4-J, S4-L, S4-P, S4-P0

SO-NP, SO-OP

**Connection diagram****Fig. 1 AC voltage endurance****Fig. 2 DC load limit curve****Dimensions [mm]****Technical approvals, conformities**

IEC 61810; EN 60947

Type	C4-X2x/ ... V Power relays, DC application 2-pole, NO, double make			
-------------	---	--	--	--

Maximum contact load	10 A/250 V AC-1	7 A/110 V DC-1
	10 A/30 V DC-1	1,2 A/220 V DC-1

Contacts

Material	Standard	Code 0	AgNi
Rated current			10 A
Switch-on current max. (20 ms)			30 A
Switching voltage max			250 V
AC load (Fig 1)			2,5 kVA
DC load			see Fig. 2

Coil

Coil resistance	see table; tolerance $\pm 10\%$
Pick-up voltage	$\leq 0,8 \times U_N$
Release voltage	$\geq 0,1 \times U_N$
Nominal power	2,4 VA (AC)/1,3 W (DC)

Coil table

VAC	Ω	mA	VDC	Ω	mA
24	65	100	24	443	54
48	286	50	48	1K8	27
115	1K7	21	110	9K2	12
230	6k8	10	220	36K1	6

Insulation

	Volt rms, 1 min
Contact open	2500 V
Contact/contact	2,5 kV
Contact/coil	2,5 kV
Insulation resistance at 500 V	$\geq 1 \text{ G}\Omega$
Insulation, IEC 61810-1	2,5 kV/3





Specifications

Ambient temperature operation/storage	-40 (no ice)....60 °C / -40 ... 80 °C
Pick-up time/bounce time	20 ms/ $\leq 3 \text{ ms}$
Release time/bounce time	8 ms/ $\leq 1 \text{ ms}$
Mechanical life ops	AC: 10 Mill./DC: 20 Mill.
DC voltage endurance at rated load	≥ 100000 switching cycles
Switching frequency at rated load	≤ 1200 /ops/h
Protection class	IP40
Weight	90 g

Standard types**VAC 50 Hz/60 Hz: 24, 48, 115, (120), 230, (240)****LED****RC Suppressor****VDC 24, 48, 110, 220****LED****Free wheeling diode****Polarity and free wheeling diode****AC/DC bridge rectifier 24 V, 48 V, 60 V**
C4-X20/AC ... V
C4-X20X/AC ... V
C4-X20R/AC ... V
C4-X20/DC ... V
C4-X20X/DC ... V
C4-X20DX/DC ... V
C4-X20FX/DC ... V
C4-X20BX/UC ... V

"... " Enter the voltage for full type designation

Accessories
 Socket:
 Optional accessories (blanking plug):

S4-S, S4-L, S4-P, S4-P0
SO-NP, SO-OP
**Connection diagram****Fig. 1 AC voltage endurance****Fig. 2 DC load limit curve****Dimensions [mm]****Technical approvals, conformities**

IEC 61810; EN 60947


Type	C4-R3x/ ... V Magnetic remanence relay 3 change-over contact			
Maximum contact load	10 A/250 V	AC-1	0,5 A/110 V	DC-1
	10 A/10 V	DC-1	0,2 A/220 V	DC-1
Recommended minimum contact load	10 mA/10 V	Code 0, 9		
	5 mA/5 V	Code 8		

Contacts

Material	Standard	Code 0	AgNi
	Optional	Code 8	AgNi + 10 µ Au
	Optional	Code 9	AgNi + 0,2 µ Au
Rated current			10 A
Switch-on current max. (20 ms)			30 A
Switching voltage max.			250 V
AC load			2,5 kVA
DC load			see Fig. 2

Coil

Coil resistance	see table; tolerance ± 10 %
ON pulse power	1,5 VA/W
OFF pulse power	0,5 VA/W
	1 Winding for AC, 2 Windings for DC
Pull-in ON/OFF	≤ 0,8 x U _N

Internal Diagram:**Coil table**

VAC	mA ON	mA OFF	VDC	mA ON	mA OFF
24	75	12	12	125	41
48	38	6	24	63	21
115	16	2,5	48	31	10
230	8	1,3	110	14	4,5

Insulation

Contact open	Volt rms, 1 min
Contact/contact	1000 V
Contact/coil	2,5 kV
Insulation resistance at 500 V	2,5 kV
Insulation, IEC 61810-1	≥1 G.Ω
	2,5 kV/3

Specifications

Ambient temperature operation/storage	-40 (no ice)...60 °C / -40 ... 80 °C
Minimum pulse length for ON/OFF	50 ms
Mechanical life ops	AC: 10 Mill./DC: 20 Mill. switching cycles
DC voltage endurance at rated load	≥100000 switching cycles
Switching frequency at rated load	≤ 1200/h
Protection class	IP40
Weight	95 g





Standard types**VAC 50 Hz/60 Hz: 24, 48, 115 (120), 230 (240)****VDC 12, 24, 48, 110**

C4-R30/AC ... V	C4-R38/AC ... V	C4-R39/AC ... V
C4-R30/DC ... V	C4-R38/DC ... V	C4-R39/DC ... V

"... " Enter the voltage for full type designation

Accessories

Socket:	S4-J, S4-L, S4-P, S4-P0
Optional accessories (blanking plug):	SO-NP, SO-OP

**Connection diagram****Fig. 1 AC voltage endurance****Fig. 2 DC load limit curve****Dimensions [mm]****Technical approvals, conformities**

IEC 61810; EN 60947