

Rittal – The System.

Faster – better – everywhere.

Wallmounted enclosure – WM 8017.575

Date : Jan 6, 2016

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Wallmounted enclosure – WM 8017.575 - WM242412NC

created : 06.01.2016 build on www.rittal.com/ca-en



Product description


Material:	Door: Carbon steel, all-round foamed-in PU seal Housing: Carbon steel
Surface finish:	Housing and door: Dipcoat primed, powder-coated on the outside, textured paint Mounting plate: Zinc-plated
Color:	RAL 7035
Protection category IP to IEC 60 529:	IP 66
Protection category NEMA:	NEMA 4
Supply includes:	Housing with door(s) Left hand hinge Mounting plate Rear wall mounting holes Quarter turn latch with slotted head insert
Packaging unit:	1 pc(s).

Product features

Dimensions:	Height: 600 mm (24 ") Width: 600 mm (24 ") Depth: 300 mm (12 ")
Mounting plate:	Height: 570 mm (22 ") Width: 549 mm (22 ")

Weight/pack: 28 kg (61.7 lb.)

Approvals

Approvals:  [UL \(EN\)](#)

Downloads

Data sheets: [Graphics \(US\)](#)

Documentation:  [Further information \(US\)](#)
 [Info sheet \(US\)](#)

CAD drawings: [Request](#)