# Product data sheet Characteristics

# P4GC

# APC Power-Saving Timer Essential SurgeArrest, 4 Outlet Wall Tap, 120V





#### Overview

Lead time Usually in Stock

#### General

Provided equipment	User Manual

#### Physical

Color	White	
Depth	2.01 in (5.1 cm)	
Height	6.50 in (16.5 cm)	
Product Weight	0.55 lb(US) (0.25 kg)	
Width	3.70 in (9.4 cm)	

#### Input

Input Frequency	50/60 Hz
Plug standard	NEMA 5-15P
Maximum Input Current per Phase	15 A
Nominal Input Voltage	120 V

## Output

Number of power socket outlets	4
Outlet standard	NEMA 5-15R

#### Conformance

UL 1449 TVSS Rating	400	
Product Certifications	ETL	
Standards	UL 1449	
Equipment protection policy	Lifetime: \$50000	

## Environmental

Ambient Air Temperature for Operation	32113 °F (045 °C)
Relative Humidity	095 %
Operating altitude	010000 ft
Ambient Air Temperature for Storage	23113 °F (-545 °C)
Storage Relative Humidity	095 %
Storage altitude	050000 ft (0.0015240.00 m)

## Surge Protection and Filtering

NM Surge Response Time (ns)	1 ns common mode
Common mode rejection	40 dB
Peak current	72 kA common mode
Surge energy rating	1080 J

## Ordering and shipping details

Category	11309 - APC RESALE PRODUCTS
GTIN	00731304269267
Nbr. of units in pkg.	1
Package weight(Lbs)	1 lb(US) (0.45 kg)
Returnability	No
Country of origin	PH

# Packing Units

0		
Package 1 Height	9.65 in (24.5 cm)	
Package 1 width	8.90 in (22.6 cm)	
Package 1 Length	2.64 in (6.7 cm)	
SCC14	10731304269264	
Number of Units in Package 2	6	
Package 2 Weight	7.88 lb(US) (3.57 kg)	
Package 2 Height	11.68 in (296.67 mm)	
Package 2 width	12.13 in (308.10 mm)	
Package 2 Length	19.85 in (504.19 mm)	
Number of Units in Package 3	288	

## Contractual warranty

Warranty	Limited Lifetime
----------	------------------