



Main

| | |
|---------------------------------------|--|
| Range of product | Telemecanique Inductive proximity sensors XS |
| Accessory / separate part category | Mounting and fixing accessories |
| Accessory / separate part type | Bracket |
| Accessory / separate part designation | Fixing bracket |
| Accessory / separate part destination | Cylindrical M30 sensor |
| Material | Stainless steel |

Complementary

| | |
|-----------------------|-----------------------|
| Product compatibility | XS cylindrical M30 |
| Net weight | 0.18 lb(US) (0.08 kg) |

Packing Units

| | |
|------------------------------|------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 1.76 oz (50 g) |
| Package 1 Height | 2.17 in (5.5 cm) |
| Package 1 width | 1.65 in (4.2 cm) |
| Package 1 Length | 3.11 in (7.9 cm) |
| Unit Type of Package 2 | S01 |
| Number of Units in Package 2 | 15 |
| Package 2 Weight | 32.42 oz (919 g) |
| Package 2 Height | 5.91 in (15 cm) |
| Package 2 width | 5.91 in (15 cm) |
| Package 2 Length | 15.75 in (40 cm) |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End of Life Information |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|