8538SCG11V02S

NEMA combination starter, Type S, nonfusible disconnect, Size 1, 27A, 10HP at 600VAC, 3 phase, 3 pole, melting alloty, 120VAC coil, NEMA 1



Main

Wall		
Product	Combination Starter	
Туре	S	
Control Circuit Type	Separate control circuit	

Complementary

Control Circuit Voltage	110 V AC 50 Hz	
oom or on our voilage	120 V AC 60 Hz	
Starter Type	Non reversing	
Number of Poles	3P	
Horsepower Rating	7.5 Hp 200 V AC, 3 phase	
	7.5 Hp 230 V AC, 3 phase	
	10 Hp 460 V AC, 3 phase	
	10 hp 575 V AC, 3 phase	
Maximum Voltage Rating	600 V AC	
Control Units	No control units	
Pilot Light	No indicator	
Auxiliary Contacts	Without	
Thermal overload type	Melting alloy 3	
Disconnect Type	Non-fusible disconnect switch	
NEMA size	1	

Environment

Enclosure Type	NEMA 1 painted sheet steel with external reset

Ordering and shipping details

Category	21213-8538,39 SC,SD(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	785901744368
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	10.70 in (27.178 cm)	
Package 1 Width	13.20 in (33.528 cm)	
Package 1 Length	29.00 in (73.66 cm)	
Package 1 Weight	34.35 lb(US) (15.581 kg)	

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Not compliant
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------