Rittal - The System.

Faster – better – everywhere.

Wallmounted enclosure – WM 8017.530

Date : Oct 2, 2017



ENCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

Wallmounted enclosure - WM 8017.530 - WM161606NC

: 02.10.2017 build on www.rittal.com/ca-en



| | | 4 1 | | | |
|----|------|------|--------------|---------|---|
| Pr | udii | ct d | ASCI | riptior | ì |
| | vuu | ot u | 530 1 | . Puoi | |

Material: Door: Carbon steel, all-round foamed-in PU seal

Housing: Carbon steel

Surface finish: Housing and door: Dipcoat primed, powder-coated on the outside, textured paint

Mounting plate: Zinc-plated

Color: RAL 7035

Protection category IP to IEC 60 529:

IP 66

Protection category

NEMA:

NEMA 4

Supply includes: Housing with door(s)

Left hand hinge Mounting plate

Rear wall mounting holes

Quarter turn latch with slotted head insert

Product features

Dimensions: Height: 400 mm (16 ")

Width: 400 mm (16 ") Depth: 150 mm (5.9 ")

Material thickness:: Housing: 1.5 mm (0.06 ")

Door: 1.5 mm (0.06 ")

Mounting plate: 1.5 mm (0.06 ")

Mounting plate: Height: 375 mm (15 ")

Width: 354 mm (14 ")

© Rittal 2017

| Packaging unit: | 1 pc(s). | |
|---------------------------|----------------|--|
| Weight/packaging unit: | 10 kg (22 lb.) | |
| EAN: | 83117 | |
| Approvals | | |
| Approvals: | UL | |

© Rittal 2017 2