

# Product Datasheet

## Characteristic

# XS508B1PAL2

inductive sensor XS5 M8 - L33mm - stainless - Sn1.5mm - 12..24VDC - cable 2m



## Main

range of product	OsiSense XS
series name	general purpose
sensor type	inductive proximity sensor
device application	-
sensor name	XS5
sensor design	cylindrical M8
size	33 mm
body type	fixed
detector flush mounting acceptance	flush mountable
material	metal
type of output signal	discrete
wiring technique	3-wire
[Sn] nominal sensing distance	0.06 in (1.5 mm)
discrete output function	1 NO
output circuit type	DC
discrete output type	PNP
electrical connection	cable
cable length	6.56 ft (2 m)
[Us] rated supply voltage	12...24 V DC with reverse polarity protection
switching capacity in mA	<= 200 mA DC with overload and short-circuit protection
IP degree of protection	IP67 conforming to IEC 60529

## Complementary

thread type	M8 x 1
detection face	frontal
front material	PPS
enclosure material	nickel plated brass
operating zone	0...0.05 in (0...1.2 mm)
differential travel	1...15% of Sr

cable composition	3 x 0.11 mm <sup>2</sup>
wire insulation material	PvR
status LED	1 LED yellow output state
supply voltage limits	10...36 V DC
switching frequency	<= 5000 Hz
voltage drop	<= 2 V (closed state)
current consumption	<= 10 mA, no-load
delay first up	<= 10 ms
delay response	<= 0.1 ms
delay recovery	<= 0.1 ms
marking	CE
threaded length	0.98 in (25 mm)
height	0.31 in (8 mm)
length	1.3 in (33 mm)
product weight	0.08 lb(US) (0.035 kg)

## Environment

product certifications	CSA UL
ambient air temperature for operation	-13...158 °F (-25...70 °C)
ambient air temperature for storage	-40...185 °F (-40...85 °C)
vibration resistance	25 gn, amplitude: +/- 2 mm (f = 10...55 Hz) conforming to IEC 60068-2-6
shock resistance	50 gn (duration = 11 ms) conforming to IEC 60068-2-27

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0953 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Available