# QO3201021

Mini circuit breaker, QO, 20A, 3 pole, 120/240VAC, 10kA, plug in mount, AC shunt





#### Main

Product	Miniature circuit-breaker
Range	QO
Current Rating	20 A
Voltage Rating	120/240 V AC 240 V AC
	120 V AC
Mounting Type	Plug-in
Number of Poles	3P
Circuit Breaker Type	Standard
Ratings	HACR rated
Electrical Connection	Pressure plate
Options	Shunt trip 120/208/240 V AC

#### Complementary

10 KA 120/240 V AC 50/60 Hz 10 KA 240 V AC 50/60 Hz 10 kA 120 V AC 50/60 Hz	
4	
AWG 14AWG 8 copper or aluminium	
35.40 lbf.in (4 N.m)	
2.99 in (76 mm)	
2.99 in (76 mm)	
2.91 in (74 mm)	
1.19 lb(US) (0.540 kg)	
	10 KA 240 V AC 50/60 Hz 10 kA 120 V AC 50/60 Hz 4 AWG 14AWG 8 copper or aluminium 35.40 lbf.in (4 N.m) 2.99 in (76 mm) 2.99 in (76 mm) 2.91 in (74 mm)

#### Environment

Certifications	UL Listed[RETURN]CSA
Ambient Rating	104 °F (40 °C)

### Ordering and shipping details

Category	00012-QO 3 POLE CIRCUIT BREAKER
Discount Schedule	DE2A
GTIN	785901494096
Returnability	No
Country of origin	MX

### **Packing Units**

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	3.20 in (8.128 cm)	
Package 1 Width	3.70 in (9.398 cm)	
Package 1 Length	4.60 in (11.684 cm)	
Package 1 Weight	19.04 oz (539.775 g)	

## Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Compliant with Exemptions	
Toxic heavy metal free	Yes	
Mercury free	Yes	
China RoHS Regulation	China RoHS Declaration	
RoHS exemption information	₫Yes	
Circularity Profile	No need of specific recycling operations	
Halogen content performance	Halogen free product	

### Contractual warranty

Warranty	18 months
----------	-----------