

23073 - GE Cool White T12

F60T12/CW 15PK

PRODUCT PHOTO



CAUTIONS & WARNINGS

Warning

Risk of Electric Shock

Turn power off before inspection

installation or removal.

Caution

Lamp may shatter and cause injury if broken

Wear safety glasses and gloves when handling lamp.

Do not use excessive force when installing lamp.



GENERAL CHARACTERISTICS

Base Description Single Pin Pin/Plug-In Base Type Mercury Content 90 mg Mercury-Picogrm per mean Im hr 2265.9 Starting Temp (MIN) C-degrees 10 °C **Bulb Material** Soda lime Rated Life Hours-nominal 12000 h **Primary Application** Full Wattage **Product Technology** Linear Fluorescent

Base Fa8
Bulb Shape T12

PHOTOMETRIC CHARACTERISTICS

Mean Lumens nominal3310 lmNominal Initial Lumen per Watt72Initial Lumens-nominal3460 lmColor Rendering Index-CRI60Color Temperature4100 K

PRODUCT INFORMATION

Product Code 23073

Description F60T12/CW 15PK

Alternative Unit Of Measure CASE

Standard Package Quantity

Ean UPC 043168981149 Standard Package GTIN 43168230735

No Of Items Per Sales Unit No Of Items Per Standard Package

Sales Unit Case

UCC 043168230735


DIMENSIONS

Bulb Diameter (DIA) <Max> 1.59 in
Bulb Diameter (DIA) <Min> 1.41 in
Diameter 1.5 in
Face to End of Opposing Pin (B) <Max> 57.65 in
Face to End of Opposing Pin (B) <Min> 57.42 in
Nominal Length 60.0 in

ELECTRICAL CHARACTERISTICS

Current Crest Factor (MAX) 1.7
Cathode Resistance Ratio - Rh/Rc (MIN) 4.250
Cathode Resistance Ratio - Rh/Rc (MAX) 6.500
Rated power (Watts) 50 W





Mar 15, 2019 8:07:53 PM | For additional information, visit products.currentbyge.com