



### Main

Device short name	XCSTE
Enclosure type	Dust and damp proof enclosure indoor/outdoor Corrosion resistance enclosure indoor/outdoor

### Complementary

[In] rated current	6 A
[Us] rated supply voltage	120 V
Actuator	Key
Contact operation	Slow-break
Contacts type and composition	2 NC
Depth	1.3 in (33.02 mm)
Electromagnet interlocking	Locking on energisation and unlocking on de-energisation of solenoid
Enclosure material	plastic
Height	3.67 in (93.22 mm)
Locking options description	With interlocking, locking by solenoid With locking of actuator, unlocking by key operated lock
Number of poles	2
Permissible voltage	300 V AC

### Environment

Ambient air temperature for operation	-13...140 °F (-25...60 °C)
IP degree of protection	IP67
NEMA degree of protection	NEMA 4/4X/12

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Package 1 Weight	17.64 oz (500 g)
Package 1 Height	4.33 in (11 cm)
Package 1 width	1.38 in (3.5 cm)
Package 1 Length	3.74 in (9.5 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>