# AP7530 Rack PDU, Basic, Zero U, 20A, 120V, (24)5-20







#### Overview

Lead time Usually in Stock

#### General

Provided Equipment	Cord retention bracket(s) Installation guide
	Rack Mounting brackets
	Toolless Mounting Kit
	User Manual

### Physical

Cable length	10 ft (3.05 m)	
Color	Black	
Depth	1.73 in (4.4 cm)	
Height	63.74 in (161.9 cm)	
Product Weight	10.71 lb(US) (4.86 kg)	
Width	2.20 in (5.6 cm)	

#### Input

Line Rated Current	16 A	
Permissible voltage	100120 V	
Input current limits	20 A	
Load Capacity	1920 VA	
Input Frequency	50/60 Hz	
Plug standard	NEMA L5-20P	
Nominal Input Voltage	100 V 120 V	

#### Output

Number of power socket outlets	24 NEMA 5-20R

#### Conformance

Product Certifications	CUL Listed UL Listed
Standards	CSA C22.2 No. 60950-1-03 UL 60950-1

### Environmental

Ambient Air Temperature for Operation	23113 °F (-545 °C)	
Relative Humidity	595 %	
Operating altitude	015000 ft	
Ambient Air Temperature for Storage	-13149 °F (-2565 °C)	
Storage Relative Humidity	595 %	
Storage altitude	050000 ft (0.0015240.00 m)	

# Ordering and shipping details

Category	11309 - APC RESALE PRODUCTS
GTIN	00731304207962
Nbr. of units in pkg.	1
Package weight(Lbs)	1 lb(US) (0.45 kg)
Returnability	No
Country of origin	IN

# Packing Units

Package 1 Height	84.02 in (213.4 cm)
Package 1 width	5.98 in (15.2 cm)
Package 1 Length	5.00 in (12.7 cm)
SCC14	731304207962

# Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	☑ REACh Declaration	
EU RoHS Directive	Compliant EEU RoHS Declaration	
Lead free	Yes	
Optimized Energy Efficiency	Energy efficient product	
Take-back	Take-back program available	

## Contractual warranty

Some actual Warranty		
Warranty	2 years repair or replace	