
# NSYMR33

# Monobloc perforated plates H300xW300mm with universal perforations 11x26mm





### Main

Range	Spacial
Accessory / separate part category	Mounting accessory
Product or Component Type	Mounting plate
Device Application	Multi-purpose
Enclosure nominal dimensions	- H: 11.81 in (300 mm) W: 11.81 in (300 mm)
Mounting Location	Step slide Direct fixing on backstuds
Mounting plate description	Telequick perforated
Range compatibility	Spacial Spacial S3D Spacial Spacial CRN Spacial Spacial S3X Thalassa Thalassa PLM
Quantity per Set	Set of 1
Material	steel
Surface Finish	Zinc coated

# Complementary

Screwed on backstuds M8 By fixing element	
10.04 in (255 mm)	
9.88 in (251 mm)	
0.59 in (15 mm)	
0.08 in (2 mm)	
1.12 lb(US) (0.506 kg)	
144	
Installation in rear of enclosure	
11 x 26 mm	
	By fixing element  10.04 in (255 mm)  9.88 in (251 mm)  0.59 in (15 mm)  0.08 in (2 mm)  1.12 lb(US) (0.506 kg)  144  Installation in rear of enclosure

#### Ordering and shipping details

0 11 0	
Category	80036-ENCLOSURE SYSTEMS ACCESSORIES
Discount Schedule	ES1
GTIN	3606480183621
Returnability	No
Country of origin	FR

#### **Packing Units**

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	0.67 in (1.7 cm)	
Package 1 Width	9.88 in (25.1 cm)	
Package 1 Length	10.04 in (25.5 cm)	
Package 1 Weight	18.06 oz (512 g)	
Unit Type of Package 2	PAM	
Number of Units in Package 2	276	

Package 2 Height	19.69 in (50 cm)
Package 2 Width	39.37 in (100 cm)
Package 2 Length	47.24 in (120 cm)
Package 2 Weight	354.94 lb(US) (161 kg)
Sustainable offer status	
Offer Sustainability	
Sustainable offer status	Green Premium product
	Green Premium product  REACh Declaration
REACh Regulation REACh free of SVHC	

	Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
China RoHS Regulation	China RoHS Declaration	
RoHS exemption information	€Yes	
Environmental Disclosure	Product Environmental Profile	

# Contractual warranty

Circularity Profile

Warranty	18 months
ranany	To monate

No need of specific recycling operations