### UC1AAA2



Uniprise Ultra 10® Category 6A U/UTP Patch Cord, Snagless

#### **Product Classification**

Regional Availability North America

Portfolio Uniprise®

Product Type Twisted pair patch cord

Product Brand Ultra 10®

Product Series UC

Ordering Note Cords < 1 m are valid elements for use in a channel or as an equipment interconnect but

due to their limited length are not guaranteed to meet component compliance requirements that were developed to assess the quality of longer cords | Cords > 1 m are authorized for use in channels and are an effective standalone method used to connect active devices

#### General Specifications

ANSI/TIA Category 6A

Cable Type U/UTP (unshielded)

Conductor Type Solid

Interface, Connector ARJ45 plugInterface Feature, connector AStandardInterface, Connector BRJ45 plugInterface Feature, connector BStandard

Jacket Color Black | Blue | Green | Orange | Purple | Red | Slate | Violet | White | Yellow

Pairs, quantity 4

**Transmission Standards** IEEE 802.3bt Type 4

Wiring T568B

**Dimensions** 

Cable Assembly Length Range (m) 1 – 30

**COMMSCOPE®** 

## UC1AAA2

Cable Assembly Length Range (ft) 1 - 100

Cable Assembly Length Range (cm) 15 - 999

Cable Assembly Length Range (in) 6 - 999

**Diameter Over Jacket** 7.24 mm | 0.285 in

### Wiring Diagram

	Connector A	Connector B
Position 1	White/Orange	White/Orange
Position 2	Orange	Orange
Position 3	Lt. Green	Lt. Green
Position 4	Blue	Blue
Position 5	Lt. Blue	Lt. Blue
Position 6	Green	Green
Position 7	Lt. Brown	Lt. Brown
Position 8	Brown	Brown

#### **Electrical Specifications**

Material Specifications

**Contact Plating Material** Precious metals

Material Type Copper alloy | Polycarbonate

Mechanical Specifications

Plug Insertion Life, minimum 750 times

Plug Retention Force, minimum 133 N | 29.9 lbf

**Environmental Specifications** 

**Operating Temperature**  $-10 \,^{\circ}\text{C} \text{ to } +60 \,^{\circ}\text{C} \text{ (+14 }^{\circ}\text{F to } +140 \,^{\circ}\text{F)}$ 

**Environmental Space** Non-plenum Flammability Rating UL 94 V-0

COMMSCOPE®

# UC1AAA2

Safety Standard ETL | cETL

Packaging and Weights

Packaging quantity

Regulatory Compliance/Certifications

Agency Classification

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system

