



Main

Range of product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCKD
Head type	Rotary head
Product compatibility	XCKS
Associated body	ZCKS7 ZCKSD39H29 ZCKSD37H29 ZCKSD35H29 ZCKS6H29 ZCKS9H29 ZCKS1 ZCKS2 ZCKS6 ZCKS2H29 ZCKSD37 ZCKS8H29 ZCKSD35 ZCKS5 ZCKS1H29 ZCKSD39 ZCKS5H29 ZCKS8 ZCKS9 ZCKSD31H29 ZCKSD31 ZCKS7H29
Movement of operating head	Rotary
Type of operator	Roller lever spring return metal ball bearing mounted)
Type of approach	Lateral approach, 2 directions

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Complementary

Switch actuation	By 30° cam
Positive opening	With
Head material	Plastic

Environment

Ambient air temperature for operation	-13...158 °F (-25...70 °C)
Ambient air temperature for storage	-40...158 °F (-40...70 °C)
Environmental characteristic	Standard environment

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	3.28 oz (93 g)
Package 1 Height	1.34 in (3.4 cm)
Package 1 width	2.48 in (6.3 cm)
Package 1 Length	2.99 in (7.6 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------