



Main

Product or component type	Single Throw Safety Switch
Disconnecter device type	Fusible disconnect
Number of poles	3
Electrical connection	Lugs
Series name	Heavy duty

Complementary

Line Rated Current	600 A
Device composition	Neutral (factory installed)
Device mounting	Surface
[Ue] rated operational voltage	240 V DC 250 V AC
AWG gauge	AWG 3/0...500 kcmil copper or aluminium
Maximum Horse Power Rating	75 Hp at 240 V AC 50...60 kHz for 3 phases motors conforming to NEC 240.6 200 Hp at 240 V AC 50...60 kHz for 3 phases motors conforming to NEC 430.52 50 hp 250 V DC
Height	50.31 in (1277.87 mm)
Maximum Width	27.88 in (708.15 mm)
Depth	10.13 in (257.30 mm)
Tightening torque	375 lbf.in (42.37 N.m) AWG 3/0...500 kcmil)

Environment

Product certifications	CSA
NEMA degree of protection	NEMA 3R galvanized steel

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
PVC free	Yes
Halogen content performance	Halogen free plastic parts product