



### Main

Range of product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCE
Head type	Multi-directional head
Product compatibility	XCKT XCKD XCKP XCMD
Associated body	ZCMD37L5 ZCD35 ZCD21 ZCMD81L2 ZCT27P16 ZCT28G11 ZCT26N12 ZCT28P16 ZCMD21L5 ZCMD29L1 ZCP21M12 ZCMD69C12 ZCP37 ZCMD61M12 ZCP27 ZCMD39L2 ZCT27G11 ZCMD29L5 ZCD37 ZCMD29C12 ZCD27 ZCMD21L08U78 ZCD28 ZCMD61C12 ZCP25 ZCP29M12

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

ZCMD21L2  
 ZCT26P16  
 ZCMD41L1  
 ZCMD81L5  
 ZCT26G11  
 ZCP21  
 ZCMD41L2  
 ZCT27N12  
 ZCT25P16  
 ZCP31  
 ZCT25N12  
 ZCP39  
 ZCP29  
 ZCP28  
 ZCD21M12  
 ZCMD81L1  
 ZCD29  
 ZCMD21L08R12  
 ZCMD25L2  
 ZCT21G11  
 ZCMD29L2  
 ZCMD41L5  
 ZCD26  
 ZCT28N12  
 ZCP35  
 ZCMD39L1  
 ZCD25  
 ZCMD25L1  
 ZCMD21C12  
 ZCT25G11  
 ZCD31  
 ZCT21N12  
 ZCMD21L1  
 ZCD39  
 ZCMD21M12  
 ZCMD37L1  
 ZCD29M12  
 ZCMD37L2  
 ZCMD25L5  
 ZCMD39L5  
 ZCP26  
 ZCT21P16

Movement of operating head	Multi-directional
Type of operator	Side cat's whisker spring return metal with nitrile boot)
Type of approach	Multi-directional approach

### Complementary

Switch actuation	By any moving part
Positive opening	Without

### Environment

Ambient air temperature for operation	-13...158 °F (-25...70 °C)
Ambient air temperature for storage	-40...158 °F (-40...70 °C)
Environmental characteristic	Standard environment

### Packing Units

Package 1 Weight	0.11 lb(US) (0.052 kg)
Package 1 Height	0.170 dm
Package 1 width	1.650 dm
Package 1 Length	0.320 dm

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

### Contractual warranty

Warranty	18 months
----------	-----------