## NSYSM1812502DP

# Spacial SM compact enclosure with mounting plate - 1800x1200x500 mm





Main	
Range	Spacial
Product name	Spacial SM
Product or Component Type	Compact enclosure
Application	Multi-purpose
Installation accessory type	Floor-standing
Device composition	<ul> <li>1 body</li> <li>2 door</li> <li>2 cable gland plate</li> <li>1 locking system with handle door</li> <li>1 blocking system left door</li> <li>4 mounting plate bracket</li> <li>1 mounting plate</li> </ul>
Removable parts	Door by screws hinge Mounting plate by screws mounting plate bracket Mounting plate bracket by screws
Enclosure nominal height	70.87 in (1800 mm)
Enclosure nominal width	47.24 in (1200 mm)
Enclosure nominal	19.69 in (500 mm)

#### Complementary

Number of doors	Front 2	
Door opening side	Left 120 °) Right 120 °)	
Door type	Solid	
Lock type	4 points lock, handle with 5 mm double bar insert	
Body type	Front part forming a rigid frame with welded corners Single piece body with welded rear panel	
Mounting plate description	Plain	
Type of gland plate	Standard	
Cable entry	1 entry	
Material	Mounting plate galvanised steel Body sheet steel Door sheet steel Hinge zamak	
Surface finish	Epoxy-polyester powder	
Color	Enclosure Gray RAL 7035) Handle Black RAL 9005)	
Accessibility for operation	Front	
Net Weight	359.35 lb(US) (163 kg)	

depth

#### Environment

Standards	IEC 62208
Product Certifications	DNV[RETURN]UL[RETURN]BV
IK degree of protection	IK10 IEC 62262
IP degree of protection	IP55 IEC 60529

## Ordering and shipping details

80035-ENCLOSURE SYSTEMS FLOOR MOUNT
ES1
00785901504474
No
ES

### Packing Units

1
ı
75.98 in (193.0 cm)
49.02 in (124.5 cm)
23.23 in (59.0 cm)
359.35 lb(US) (163.0 kg)

## Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	<sup>™</sup> China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

#### Contractual warranty

Warranty	18 months	