


Butted Seam Barrel


22-18 WIRE RANGE

.032 Stock

Stamped out of the finest quality electrolytic copper, the terminal barrel is rolled and the seam is butted. Terminals employ the full barrel length that eliminates costly and time consuming location when crimping. Non-insulated and using a one-piece design, it is the most economical style and is ideal for the greatest variety of applications, where special features are not required.



Copper Solid and Stranded Wire Only



For Flanged or Locking Styles-Contact Techspan



Stud Size Part Number



4-6 R1A6S



4-6 R1A6



6-8 R1A8



8-10 R1A10



12-1/4 R1A14S



1/4-5/16 R1A56S



5/16-3/8 R1A38



4-6 BS1A6S Block Spade



4-6 BS1A6



8 BS1A8

Stud Size Part Number




10 BS1A10



Parallel P1A



Butt B1A



DIMENSIONAL CHART		
Part Number	W	L
B1A		0.570"
BS1A10	0.314"	0.615"
BS1A6	0.293"	0.619"
BS1A6S	0.246"	0.625"
BS1A8	0.312"	0.642"
R1A10	0.310"	0.697"
R1A14	0.530"	0.943"
R1A14S	0.460"	0.907"
R1A38	0.530"	0.940"
R1A56	0.531"	0.938"
R1A56S	0.460"	0.906"
R1A6	0.254"	0.642"
R1A6S	0.224"	0.545"
R1A8	0.313"	0.702"

Add suffix "M" for 1000 pack

Add suffix "P" for Pro Pack (Quantities vary by Part #)

Approved installation tool: RHT-1992/192840014

Economy installation tools: RAT-NINS, 453, HTS1000

See pages E-2 to E-5 for installation tools.