

IC425-MED

4.25" IC HOUSING - PAR16/PAR20 AIRTIGHT



NAME:

TYPE:

DATE:

NOTES:

SPECIFICATIONS

VOLTAGE: 120V

HOUSING DETAILS: These compact housings are built for ceilings with insulation. They may be used in new construction, remodeling or acoustic tile applications.

Adjustable mounting bars allow for installation between 14.25" (360mm) to 26.00" (660mm). Can be installed in ceilings up to 2.00" (50mm) thick.

For use with a PAR20 or MRE26 (PAR16) style bulb, in either a halogen or LED type. Refer to trim model for specific bulb wattages.

Socket, Quick Connect wire connectors and built-in thermal protection included.

Approved for humid locations, housing completely sealed, stops any air exchange within the ceiling cavity. Although this product is AIR-TIGHT rated, some municipalities will require the use of a vapor barrier (VP99). Verify local building codes prior to installation.

For a shower applications, a maximum of a 35W bulb may be installed.

COMPATIBLE TRIMS: TR1325 - 4.25" PAR20 SHOWER TRIM
TR1350 - 4.25" PAR20 GIMBAL TRIM
TR1510 - 4.25" PAR16 REGRESSED TRIM
TR1530 - 4.25" PAR16 GIMBAL TRIM

CUTTING HOLE: 4.38" (111.3mm)

WARRANTY: 1 year

HEIGHT: 6" (152.4mm)

LENGTH: 8.5" (215.9mm)

WIDTH: 6.25" (158.8mm)


APPLICATIONS

Ideal for high "energy efficient" construction.

IC425-MED

4.25" IC HOUSING - PAR16/PAR20 AIRTIGHT

DIMENSIONS



RATINGS



ORDERING GUIDE

IC425-MED SERIES

Series	Product
IC425-MED	4.25" Insulated Ceiling Housing-PAR20 / PAR16
Notes:	Configure product using BOLD options: Ex: IC425-MED