Product data sheet Characteristics

VW3M1C20R10 LXM28 STO connection cable 1m



Main	
Range of Product	Lexium 28
Product or Component Type	Safe torque off cable
Accessory / separate part type	Preassembled STO cordset
Accessory / separate part category	Connection accessory
Product compatibility	Servo drive LXM28
Accessory / separate part destination	Between servo drive and logic controller
Range Compatibility	Lexium 28
Cable length	3.28 ft (1 m)

Complementary

Electrical connection	Connector - Molex 4-pin servo drive side Free end CN9 interface
Net Weight	0.22 lb(US) (0.1 kg)

Ordering and shipping details

Category	18263-LEXIUM 32 ACCESSORIES	
Discount Schedule	PC51	
GTIN	3606480736032	
Returnability	No	
Country of origin	TN	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	0.59 in (1.500 cm)
Package 1 Width	6.69 in (17.000 cm)
Package 1 Length	7.09 in (18.000 cm)
Package 1 Weight	2.50 oz (71.000 g)
Unit Type of Package 2	S02
Number of Units in Package 2	20
Package 2 Height	5.91 in (15.000 cm)
Package 2 Width	11.81 in (30.000 cm)
Package 2 Length	15.75 in (40.000 cm)
Package 2 Weight	3.90 lb(US) (1.770 kg)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EPEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	₫Yes
PVC free	Yes