

Product Datasheet

Characteristic

XSAV11801TF

Rot. monitoring - M30 - Sn10mm -
6..150c/mn - 24..240VAC/DC - cable 2m



Main

range of product	OsiSense XS
series name	Application
sensor type	Inductive proximity sensor
device application	Rotation monitoring
sensor name	XSA
sensor design	Cylindrical M30
size	81 mm
body type	Fixed
detector flush mounting acceptance	Flush mountable
material	Metal
enclosure material	Nickel plated brass
type of output signal	Discrete
wiring technique	2-wire
[Sn] nominal sensing distance	0.39 in (10 mm)
discrete output function	1 NC
output circuit type	AC/DC
electrical connection	Cable
cable length	6.56 ft (2 m)
[Us] rated supply voltage	24...210 V DC 24...240 V AC 50/60 Hz
switching capacity in mA	5...200 mA DC 5...350 mA AC
IP degree of protection	IP67 IEC 60529

Complementary

thread type	M30 x 1.5
detection face	Frontal
front material	PPS
adjustable frequency range	6...150 cyc/mn
operating zone	0.00...0.31 in (0...8 mm)
differential travel	3...15% of Fr

repeat accuracy	3% of Sr
cable composition	2 x 0.34 mm ²
wire insulation material	PvR
status LED	Output state 1 LED red)
supply voltage limits	20...264 V AC/DC
maximum residual current	1.5 mA open state
switching frequency	<= 100 Hz
maximum voltage drop	<5.7 V closed)
run-up delay at power-up	9 s standard
marking	CE
threaded length	2.24 in (57 mm)
height	1.18 in (30 mm)
length	3.19 in (81 mm)
product weight	0.66 lb(US) (0.3 kg)

Environment

product certifications	UL CCC CSA
ambient air temperature for operation	-40...158 °F (-40...70 °C)
ambient air temperature for storage	-40...185 °F (-40...85 °C)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	Free of Substances of Very High Concern above the threshold
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	ENVPEP111006EN
Circularity Profile	ENVEOLI111004EN