# **GV2G272**

# Linergy FT - Comb busbar - 63 A - 2 tap-offs - 72 mm pitch





## Main Range

| Range                                       | Linergy                                    |
|---|--|
| Product name                                | FT   |
| Device short name                           | GV2G                                       |
| Product or Component<br>Type                | Comb busbar                                |
| Accessory / separate part category          | Connection accessory                       |
| Poles description                           | 3P   |
| Range compatibility                         | TeSys D<br>TeSys GV2<br>TeSys K<br>TeSys U |
| Number of tap-offs                          | 2  |
| [lth] conventional free air thermal current | 63 A                                       |
| Connection pitch                            | 2.83 in (72 mm)                            |

## Complementary

| Mounting Location             | On terminal           |
|-------------------------------|-----------------------|
| [Ui] Rated Insulation Voltage | 690 V                 |
| Length                        | 4.57 in (116 mm)      |
| Net Weight                    | 0.11 lb(US) (0.05 kg) |

## Ordering and shipping details

| - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 |                                  |
|---|----------------------------------|
| Category                                | 22367-MANUAL STR PROTECTOR - GV2 |
| Discount Schedule                       | l11                              |
| GTIN                                    | 3389110555929                    |
| Returnability                           | No                               |
| Country of origin                       | RO                               |

#### **Packing Units**

| · doming or mo               |                        |  |
|------------------------------|------------------------|--|
| Unit Type of Package 1       | PCE                    |  |
| Number of Units in Package 1 | 1                      |  |
| Package 1 Height             | 0.39 in (1.0 cm)       |  |
| Package 1 Width              | 1.30 in (3.3 cm)       |  |
| Package 1 Length             | 4.61 in (11.7 cm)      |  |
| Package 1 Weight             | 1.62 oz (46.0 g)       |  |
| Unit Type of Package 2       | S01                    |  |
| Number of Units in Package 2 | 40                     |  |
| Package 2 Height             | 5.91 in (15.0 cm)      |  |
| Package 2 Width              | 5.91 in (15.0 cm)      |  |
| Package 2 Length             | 15.75 in (40.0 cm)     |  |
| Package 2 Weight             | 4.50 lb(US) (2.039 kg) |  |

## Offer Sustainability

| Sustainable offer status   | Green Premium product          |
|----------------------------|--------------------------------|
| REACh Regulation           | ☑ REACh Declaration            |
| REACh free of SVHC         | Yes                            |
| EU RoHS Directive          | Compliant EEU RoHS Declaration |
| Toxic heavy metal free     | Yes                            |
| Mercury free               | Yes                            |
| China RoHS Regulation      | ☑ China RoHS Declaration       |
| RoHS exemption information | ₽¥Yes                          |
| Environmental Disclosure   |                                |
| Circularity Profile        | End Of Life Information        |
|                            |                                |


## Contractual warranty

| Warranty | 18 months |
|----------|-----------|
|----------|-----------|

#### Sets of Busbars GV2G ••• with Terminal Block GV1G09



Sets of Busbars GV2G245, GV2G254, GV2GR272



|                     | I   |
|---------------------|-----|
| GV2G245 (2 x 45 mm) | 89  |
| GV2G254 (2 x 54 mm) | 98  |
| GV2G272 (2 x 72 mm) | 116 |