

# BMH1003T17F1A

servo motor BMH, Lexium 32, 8.2Nm,  
6000rpm, keyed shaft, with brake, IP54, 16  
multiturn encoder, straight



## Main

|                           |                                                                |
|---------------------------|----------------------------------------------------------------|
| Product or Component Type | Servo motor                                                    |
| Device short name         | BMH                                                            |
| Maximum mechanical speed  | 6000 rpm                                                       |
| Continuous stall torque   | 72.58 lbf.in (8.2 N.m) LXM32.D30M2 10 A, 230 V, single phase   |
| Peak stall torque         | 201.80 lbf.in (22.8 N.m) LXM32.D30M2 10 A, 230 V, single phase |
| Nominal output power      | 1450 W LXM32.D30M2 10 A, 230 V, single phase                   |
| Nominal torque            | 49.56 lbf.in (5.6 N.m) LXM32.D30M2 10 A, 230 V, single phase   |
| Nominal speed             | 2500 rpm LXM32.D30M2 10 A, 230 V, single phase                 |
| Product compatibility     | LXM32.D30M2 230 V single phase                                 |
| Shaft end                 | Keyed                                                          |
| IP Degree of Protection   | IP54 standard                                                  |
| Speed feedback resolution | 32768 points/turn x 4096 turns                                 |
| Holding brake             | With                                                           |
| Mounting Support          | International standard flange                                  |
| Electrical Connection     | Straight connectors                                            |

## Complementary

|                                 |                                    |
|---------------------------------|------------------------------------|
| Range Compatibility             | Lexium 32                          |
| [Us] rated supply voltage       | 240 V                              |
| Phase                           | Three phase                        |
| Continuous stall current        | 10 A                               |
| Continuous power                | 2.62 W                             |
| Maximum current Irms            | 30 A LXM32.D30M2                   |
| Maximum permanent current       | 33.85 A                            |
| Second shaft                    | Without second shaft end           |
| Shaft diameter                  | 0.75 in (19 mm)                    |
| Shaft length                    | 1.57 in (40 mm)                    |
| Key width                       | 1.18 in (30 mm)                    |
| Feedback type                   | Multiturn SinCos Hiperface         |
| Holding torque                  | 79.66 lbf.in (9 N.m) holding brake |
| Motor flange size               | 3.94 in (100 mm)                   |
| Number of motor stacks          | 3                                  |
| Torque constant                 | 0.851 N.m/A 248 °F (120 °C)        |
| Back emf constant               | 54.8 V/krpm 248 °F (120 °C)        |
| Number of motor poles           | 10                                 |
| Rotor inertia                   | 10.3 kg.cm <sup>2</sup>            |
| Stator resistance               | 0.47 Ohm 68 °F (20 °C)             |
| Stator inductance               | 3 mH 68 °F (20 °C)                 |
| Stator electrical time constant | 6.4 ms 68 °F (20 °C)               |

|                                       |                                                                                         |
|---------------------------------------|-----------------------------------------------------------------------------------------|
| Maximum radial force Fr               | 1050 N 1000 rpm<br>830 N 2000 rpm<br>730 N 3000 rpm<br>660 N 4000 rpm<br>610 N 5000 rpm |
| Maximum axial force Fa                | 0.2 x Fr                                                                                |
| Brake pull-in power                   | 18 W                                                                                    |
| Type of cooling                       | Natural convection                                                                      |
| Length                                | 9.22 in (234.3 mm)                                                                      |
| Centring collar diameter              | 3.74 in (95 mm)                                                                         |
| Centring collar depth                 | 0.14 in (3.5 mm)                                                                        |
| Number of mounting holes              | 4                                                                                       |
| Mounting holes diameter               | 0.35 in (9 mm)                                                                          |
| Circle diameter of the mounting holes | 4.53 in (115 mm)                                                                        |
| Net Weight                            | 17.97 lb(US) (8.15 kg)                                                                  |

### Ordering and shipping details

|                   |                        |
|-------------------|------------------------|
| Category          | 18282-LEXIUM 32 MOTORS |
| Discount Schedule | PC53                   |
| GTIN              | 3606485198132          |
| Returnability     | No                     |
| Country of origin | DE                     |

### Packing Units

|                              |                        |
|------------------------------|------------------------|
| Unit Type of Package 1       | PCE                    |
| Number of Units in Package 1 | 1                      |
| Package 1 Height             | 8.66 in (22.0 cm)      |
| Package 1 Width              | 7.87 in (20.0 cm)      |
| Package 1 Length             | 15.75 in (40.0 cm)     |
| Package 1 Weight             | 18.63 lb(US) (8.45 kg) |

### Offer Sustainability

|                            |                                                                                                                                                                                                                                                                                             |
|----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                                                                                                                                                                                                                       |
| California proposition 65  | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| REACH Regulation           | <a href="#">REACH Declaration</a>                                                                                                                                                                                                                                                           |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope)                                                                                                                                                                                                                                  |
| Mercury free               | Yes                                                                                                                                                                                                                                                                                         |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>                                                                                                                                                                                                                                                      |
| RoHS exemption information | <a href="#">Yes</a>                                                                                                                                                                                                                                                                         |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>                                                                                                                                                                                                                                               |
| Circularity Profile        | No need of specific recycling operations                                                                                                                                                                                                                                                    |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.                                                                                                                                                                |
| PVC free                   | Yes                                                                                                                                                                                                                                                                                         |

### Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|