



Main

| | |
|------------------------------------|----------------------|
| Accessory / separate part category | Cabling accessory |
| Accessory / separate part type | Pre-wired connectors |
| Series name | Application |

Complementary

| | |
|--------------------------------|--------------------------------------|
| Electrical connection | Elbowed female connector M12, 4 pins |
| Cable connector fixing | Screw-on |
| Collar material | Metal |
| Status LED | Without |
| Cable length | 6.56 ft (2 m) |
| Cable outer diameter | 0.23 in (5.9 mm) |
| Cable composition | 4 x 0.34 mm ² |
| Wire insulation material | PUR shielded cable) |
| [Ue] rated operational voltage | 250 V AC 300 V DC |
| [In] rated current | 4 A |
| Contact resistance | 5000 µOhm |
| Minimum insulating resistance | 1 GΩ |
| Net weight | 0.44 lb(US) (0.2 kg) |

Environment

| | |
|---------------------------------------|----------------------------|
| IP degree of protection | IP67 IP65 |
| Ambient air temperature for operation | -25...80 °C static |
| Ambient air temperature for storage | -13...176 °F (-25...80 °C) |

Packing Units


| | |
|------------------------------|-----------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 3.92 oz (111 g) |

| | |
|------------------------------|------------------------|
| Package 1 Height | 0.59 in (1.5 cm) |
| Package 1 width | 6.30 in (16 cm) |
| Package 1 Length | 6.30 in (16 cm) |
| Unit Type of Package 2 | S02 |
| Number of Units in Package 2 | 15 |
| Package 2 Weight | 4.37 lb(US) (1.984 kg) |
| Package 2 Height | 5.91 in (15 cm) |
| Package 2 width | 11.81 in (30 cm) |
| Package 2 Length | 15.75 in (40 cm) |

Offer Sustainability

| | |
|----------------------------|---|
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |

Dimensions



L : Length of cable

Connections and Schemes

Connector

