

SSP03XDSE20A

Surge protection device, XDSE, 200kA,
240/120 VAC HLD, 3 phase, 4 wire, SPD type
2



Main

| | |
|---------|-------------------------|
| Product | Surge protection device |
|---------|-------------------------|

Complementary

| | |
|---------------------------|---|
| Voltage Rating | 240/120 V HLD AC |
| MCOV | 150 V 320 V |
| Surge Current | 200 A per phase |
| Voltage Protection Rating | 700 V L-N 1200 V L-N 700 V L - G 1200 V L - G 600 V L - L 1000 V N - G 2000 V N - G |
| Rated Current | 20 kA |
| Number of Phases | 3 phase |
| Wiring Configuration | 4-wire |
| Height | 5.98 in (152 mm) |
| Width | 5.98 in (152 mm) |
| Depth | 3.98 in (101 mm) |

Environment

| | |
|------------------|---------|
| Enclosure Rating | NEMA 4X |
|------------------|---------|

Ordering and shipping details

| | |
|-------------------|----------------------------|
| Category | 08466-SURGE PROTECTION HWA |
| Discount Schedule | DE1B |
| GTIN | 3606486149188 |
| Returnability | No |

Packing Units

| | |
|------------------------------|------------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 5.70 in (14.478 cm) |
| Package 1 Width | 10.70 in (27.178 cm) |
| Package 1 Length | 12.80 in (32.512 cm) |
| Package 1 Weight | 3.98 lb(US) (1.805 kg) |

Offer Sustainability

| | |
|----------------------------|---|
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| EU RoHS Directive | Compliant with Exemptions |
| Mercury free | Yes |
| China RoHS Regulation |  China RoHS Declaration |
| RoHS exemption information |  Yes |