# SSP01XDSE20A

Surge protection device, XDSE, 200kA, 120/240 VAC,1 phase, 3 wire, SPD type 2



Main

Product Surge protection device

Complementary

Voltage Rating	120/240 V AC
MCOV	150 V
Surge Current	200 A per phase
Voltage Protection Rating	700 V L-N 700 V L - G 600 V L - L 1000 V N - G
Rated Current	20 kA
Number of Phases	1 phase
Wiring Configuration	3-wire (isolated ground)
Height	5.98 in (152 mm)
Width	5.98 in (152 mm)
Depth	3.98 in (101 mm)

#### Environment

Enclosure Rating	NEMA 4X
------------------	---------

### Ordering and shipping details

Category	08466-SURGE PROTECTION HWA
Discount Schedule	DE1B
GTIN	785901085034
Returnability	No
Country of origin	MX

#### **Packing Units**

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	5.98 in (15.2 cm)	
Package 1 Width	5.98 in (15.2 cm)	
Package 1 Length	3.98 in (10.1 cm)	
Package 1 Weight	3.91 lb(US) (1.774 kg)	

## Offer Sustainability

ead and ee cancer n go to
_