


Product data sheet

Characteristics

ZB2BY4915

Marked legend, Harmony XAC, legend,
30x40mm, white, forward, slow, fast



Main

Product or Component Type	Marked legend
Device application	With symbol NF E 52-124
Accessory / separate part type	Legend
Accessory / separate part category	Marking accessory

Complementary

Marking	Black forward, slow-fast white horizontal mounting)
User Language	English
Standards	NF E 52-124
Net Weight	0.00 lb(US) (0.001 kg)
Accessory / separate part destination	Pendant control station for control circuit Pendant control station for power circuit
Product Compatibility	XACA XACM XACB
Label dimensions	30 x 40 mm

Ordering and shipping details

Category	22466-PUSHBUTTON, ACCESSORIES
Discount Schedule	CS2
GTIN	3389110645613
Returnability	No
Country of origin	CZ

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	0.04 in (0.100 cm)
Package 1 Width	1.18 in (3.000 cm)
Package 1 Length	1.57 in (4.000 cm)
Package 1 Weight	0.03 oz (0.900 g)
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	0.39 in (1.000 cm)
Package 2 Width	2.76 in (7.000 cm)
Package 2 Length	2.76 in (7.000 cm)
Package 2 Weight	0.32 oz (9.000 g)
Unit Type of Package 3	S01
Number of Units in Package 3	1000
Package 3 Height	5.91 in (15.000 cm)
Package 3 Width	5.91 in (15.000 cm)

Package 3 Length	15.75 in (40.000 cm)
Package 3 Weight	2.53 lb(US) (1.147 kg)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty	18 months
----------	-----------