

Main

Actuation	CW and CCW
Actuator	Lever Arm (ordered separately)
Actuator Action	Spring Return
Ampere Rating	10A
Approvals	UL Listed File Number E42259 CCN NKCR - CSA Certified File Number LR25490 Class 3211-03 - CE Marked
Body Material	Zinc Alloy
Body Type	Standard Plug-In
Connection Type	Conduit Entrance (0.5 Inch NPT)
Contact Configuration	1 N.O./1 N.C.
Contact Form	Form Z - SPDT-DB
Contact Material	Silver Alloy
Contact Operation	Snap Action
Contact Rating	NEMA A600/Q600
Differential Travel	4 Degrees
Enclosure Rating	NEMA 1/2/4/6/6P/12/13
Head Type	Rotary
Maximum Voltage Rating	600V
Mounting Type	Front/Rear
Operating Temperature Range	-20 to 185 Degrees F
Operating Torque/Force	4 Inch-Pounds
Pilot Light	None
Pre-Travel	10 Degrees
Terminal Type	Screw Clamp
Total Travel	90 Degrees
Type	C
Type of Duty	Heavy Duty
Wire Size	#12 to #22 AWG

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.