

K-SPEC® HEAT SHRINK TUBING



Approved



Cross-Link Polyolefin

- CSA Approved
- Flame Retardant (except Clear)
- Thin Wall 2:1 Ratio
- Oper. Temp.: -45°C to 125°C
- Shrink Temp.: Start at 70°C, recovery at 120°C
- Longitudinal shrink ratio: < or = 8%



100 Foot Rolls

Part No.	DESCRIPTION 100 FOOT SPOOLS	CTN QTY
MHSP-3/64-0-C	HEAT SHRINK THIN-WALL BLACK 3/64"ID	100' SPL
MHSP-1/16-0-C	HEAT SHRINK THIN-WALL BLACK 1/16"ID	100' SPL
MHSP-3/32-0-C	HEAT SHRINK THIN-WALL BLACK 3/32"ID	100' SPL
MHSP-1/8-0-C	HEAT SHRINK THIN-WALL BLACK 1/8"ID	100' SPL
MHSP-1/4-0-C	HEAT SHRINK THIN-WALL BLACK 1/4"ID	100' SPL
MHSP-1/4-9-C	HEAT SHRINK THIN-WALL CLEAR 1/4"ID	100' SPL
MHSP-3/16-0-C	HEAT SHRINK THIN-WALL BLACK 3/16"ID	100' SPL
MHSP-3/8-0-C	HEAT SHRINK THIN-WALL BLACK 3/8"ID	100' SPL
MHSP-1/2-0-C	HEAT SHRINK THIN-WALL BLACK 1/2"ID	100' SPL
MHSP-1/2-9-C	HEAT SHRINK THIN-WALL BLACK 1/2"ID	100' SPL
MHSP-5/8-0-C	HEAT SHRINK THIN-WALL BLACK 5/8"ID	100' SPL
MHSP-5/8-9-C	HEAT SHRINK THIN-WALL BLACK 5/8"ID	100' SPL
MHSP-3/4-0-C	HEAT SHRINK THIN-WALL BLACK 3/4"ID	100' SPL

Part No.	DESCRIPTION MASTER SPOOLS	CTN QTY
MHSP-1/16-0-200M	HEAT SHRINK THIN-WALL BLACK 1/16"ID	200M SPL
MHSP-1/8-0-100M	HEAT SHRINK THIN-WALL BLACK 1/8"ID	100M SPL
MHSP-1/4-0-100M	HEAT SHRINK THIN-WALL BLACK 1/4"ID	100M SPL
MHSP-3/16-0-100	HEAT SHRINK THIN-WALL BLACK 3/16"ID	100M SPL
MHSP-3/8-0-100M	HEAT SHRINK THIN-WALL BLACK 3/8"ID	100M SPL
MHSP-1/2-0-100M	HEAT SHRINK THIN-WALL BLACK 1/2"ID	100M SPL
MHSP-5/8-0-100M	HEAT SHRINK THIN-WALL BLACK 5/8"ID	100M SPL
MHSP-3/4-0-100M	HEAT SHRINK THIN-WALL BLACK 3/4"ID	100M SPL
MHSP-1-0-50M	HEAT SHRINK THIN-WALL BLACK 1"ID	50M SPL
MHSP-1 1/4-0-50M	HEAT SHRINK THIN-WALL BLACK 1 1/4"ID	50M SPL
MHSP-1 1/2-0-40M	HEAT SHRINK THIN-WALL BLACK 1 1/2"ID	40M SPL
MHSP-2-0-25M	HEAT SHRINK THIN-WALL	25M SPL

C