

# LA2KT2U

Electronic time delay auxiliary contact block,  
TeSys K, 1C/O, on delay 1-30s, front, control  
110...240V AC



## Main

|                                                          |                                                                          |
|----------------------------------------------------------|--------------------------------------------------------------------------|
| Range                                                    | TeSys                                                                    |
| Product name                                             | TeSys K                                                                  |
| Product or Component Type                                | Time delay auxiliary contact block                                       |
| Device short name                                        | LA1                                                                      |
| Range compatibility                                      | TeSys K LC1K[RETURN]TeSys K CA2K[RETURN]TeSys K CA3K[RETURN]TeSys K CA4K |
| Mounting Location                                        | Front                                                                    |
| Pole contact composition                                 | 1 C/O                                                                    |
| Contacts operation                                       | Time delay                                                               |
| Timer type                                               | On delay                                                                 |
| Time delay range                                         | 1...30 s                                                                 |
| [Ue] rated operational voltage                           | 110...240 V AC control circuit<br>240 V AC signalling circuit            |
| Rated operational voltage limits                         | 0.85...1.1 U <sub>c</sub>                                                |
| [I <sub>th</sub> ] conventional free air thermal current | 2 A for signalling circuit                                               |
| Standards                                                | EN/IEC 60947-5-1<br>UL 60947-5-1<br>CSA C22.2 No 60947-5-1               |
| Product Certifications                                   | UL[RETURN]CSA[RETURN]CE[RETURN]UKCA                                      |

## Complementary

|                         |                                                   |
|-------------------------|---------------------------------------------------|
| Insulation resistance   | > 10 MOhm                                         |
| Connections - terminals | Slip-on terminals                                 |
| Reset time              | 1.5 S during time delay<br>0.5 s after time delay |
| Height                  | 1.06 in (27 mm)                                   |
| Width                   | 1.50 in (38 mm)                                   |
| Depth                   | 1.50 in (38 mm)                                   |
| Net Weight              | 0.09 lb(US) (0.04 kg)                             |

## Environment

|                                       |                              |
|---------------------------------------|------------------------------|
| Environmental characteristic          | Normal environment           |
| IP degree of protection               | IP20 conforming to IEC 60529 |
| Protective treatment                  | TC IEC 60068                 |
| Ambient Air Temperature for Operation | 14...140 °F (-10...60 °C)    |

## Ordering and shipping details

|                   |                               |
|-------------------|-------------------------------|
| Category          | 22341-CONTACTOR,D,K,&F ACCESS |
| Discount Schedule | I12                           |
| GTIN              | 3389110230086                 |
| Returnability     | Yes                           |
| Country of origin | TN                            |

## Packing Units

|                              |                        |
|------------------------------|------------------------|
| Unit Type of Package 1       | PCE                    |
| Number of Units in Package 1 | 1                      |
| Package 1 Height             | 1.97 in (5.000 cm)     |
| Package 1 Width              | 1.89 in (4.800 cm)     |
| Package 1 Length             | 1.89 in (4.800 cm)     |
| Package 1 Weight             | 1.55 oz (44.000 g)     |
| Unit Type of Package 2       | S02                    |
| Number of Units in Package 2 | 70                     |
| Package 2 Height             | 5.91 in (15.000 cm)    |
| Package 2 Width              | 11.81 in (30.000 cm)   |
| Package 2 Length             | 15.75 in (40.000 cm)   |
| Package 2 Weight             | 7.41 lb(US) (3.361 kg) |

## Offer Sustainability

|                            |                                                                                                                                 |
|----------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                                                           |
| REACH Regulation           | <a href="#"> REACH Declaration</a>             |
| EU RoHS Directive          | Compliant with Exemptions                                                                                                       |
| Mercury free               | Yes                                                                                                                             |
| China RoHS Regulation      | <a href="#"> China RoHS Declaration</a>        |
| RoHS exemption information | <a href="#"> Yes</a>                           |
| Environmental Disclosure   | <a href="#"> Product Environmental Profile</a> |
| Circularity Profile        | No need of specific recycling operations                                                                                        |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.    |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|