



Main

Range of Product	PacDrive 3
Product or Component Type	Power supply
Component name	LXM62

Complementary

Supply circuit type	AC
[Us] rated supply voltage	400 V three phase - 10...10 % 230 V three phase - 10...10 % 230 V single phase - 10...10 %
Supply frequency	50/60 Hz +/- 5 %
[Uc] control circuit voltage	24 V DC - 20...25 %
Power supply output current	20 A
Bus voltage	270...700 V
Maximum DC bus voltage	860 V
Maximum cable capacity	1.36 mF
Line Rated Current	10 A single phase AC 10 A three phase AC
Peak current	20 KA single phase AC 1 s 20 kA three phase AC 1 s
Nominal power	5.2 KW 400 V three phase AC 6.2 kW 480 V three phase AC
Maximum power	10.4 KW 400 V three phase AC 12.5 kW 480 V three phase AC
Holding time	15 min
Braking resistance	15 Ohm
Permanent braking power	400 W
Maximum braking power	46 kW
Output type	2 relays volt-free contacts
Physical interface	SERCOS III
Marking	CE
Safety level	Can reach SIL 2 EN 61508 Can reach PL d/category 3 EN/ISO 13849-1
Overvoltage category	III EN 61800-5-1
Depth	10.63 in (270 mm)
Width	3.52 in (89.5 mm)
Height	12.20 in (310 mm)
Net Weight	13.89 lb(US) (6.3 kg)

Environment

Standards	UL 508C EN/IEC 61800-5-1 EN/IEC 61800-3
Product Certifications	UL[RETURN]CSA
IP degree of protection	IP20 EN/IEC 60721-3-3 with plugged-in connectors)
Vibration resistance	10 m/s² EN/IEC 60721-3-3
Shock resistance	100 m/s² in operation EN/IEC 60721-3-3 300 m/s² during transport EN/IEC 60721-3-3
Pollution degree	2 EN/IEC 60721-3-3
Environmental characteristic	3K3 IEC 60721-3-3 5...85 %
Ambient air temperature for operation	104...131 °F (40...55 °C) with current derating of 2 % per °C) 41...104 °F (5...40 °C)
Ambient Air Temperature for Storage	-13...131 °F (-25...55 °C)

Ordering and shipping details

Category	18356-PACDRIVE3 LEXIM62 SERVO DRIVES
Discount Schedule	PC52
GTIN	3606485400341
Returnability	No

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.09 in (18.000 cm)
Package 1 Width	13.39 in (34.000 cm)
Package 1 Length	17.52 in (44.500 cm)
Package 1 Weight	16.06 lb(US) (7.286 kg)
Unit Type of Package 2	P06
Number of Units in Package 2	6
Package 2 Height	29.53 in (75.000 cm)
Package 2 Width	23.62 in (60.000 cm)
Package 2 Length	31.50 in (80.000 cm)
Package 2 Weight	121.25 lb(US) (55.000 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
PVC free	Yes