NSYS3D6425P

Wall mounted steel enclosure, Spacial S3D, plain door, with mounting plate, 600x400x250mm, IP66, IK10





Main	
Range	Spacial
Product name	Spacial S3D
Application	Multi-purpose
Category	Compact enclosure
Enclosure nominal height	23.62 in (600 mm)
Enclosure nominal width	15.75 in (400 mm)
Enclosure nominal depth	9.84 in (250 mm)
Door type	Solid
Mounting plate description	Plain
Type of gland plate	Standard
Installation accessory type	Wall-mounting
Device composition	1 body 1 mounting plate

1 door with lock 1 cable gland plate

Complementary

Complementary	
Body type	Single piece body Gutter-shaped front rail double sheet thickness
	Outlet-shaped from rail double sheet thickness
Number of doors	Front face 1
Door opening side	Reversible 120 °)
Lock type	3 points lock, 3 mm double-bar
Accessibility for operation	Front
Removable parts	Door by hinges
	Cable gland plate by screws Mounting plate by fixing element
	Modifiling plate by fixing element
Material	Enclosure steel
	Mounting plate galvanised steel
Surface finish	Enclosure epoxy-polyester powder
Color	Enclosure Gray RAL 7035)
Standards	IEC 62208
Product Certifications	LR[RETURN]cUL[RETURN]DNV[RETURN]UL[RETURN]GL[RETURN]BV
Net Weight	33.07 lb(US) (15 kg)

Environment

NEMA Degree of Protection	NEMA 4X/13
IK degree of protection	IK10 IEC 62262
IP degree of protection	IP66 IEC 60529

Ordering and shipping details

Category	80034-ENCLOSURE SYSTEMS WALL MOUNT METAL
Discount Schedule	ES1
GTIN	3606480159299
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	11.81 in (30.0 cm)
Package 1 Width	16.14 in (41.0 cm)
Package 1 Length	24.02 in (61.0 cm)
Package 1 Weight	31.66 lb(US) (14.361 kg)
Unit Type of Package 2	PAM
Number of Units in Package 2	27
Package 2 Height	7.87 in (20.0 cm)
Package 2 Width	39.37 in (100.0 cm)
Package 2 Length	47.24 in (120.0 cm)
Package 2 Weight	883.50 lb(US) (400.747 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty 18 months	
--------------------	--