



*Quality Products. Service Excellence.*

## Swing-Out Sectional Wall Mount Rack Cabinet *HWM Series*

UL2416 rated for up to 350 lbs (158 kg). Static Load tested to 1,400 lbs (635 kg). Seismic rated up to 200 lbs (90.72 kg).



### Features

- Available in two (2) depths and four (4) heights.
- All sizes include either a vented 63% perforated front door or a smoked window front door.
- Includes one (1) pair of 10-32 threaded rack rails with support for additional optional rails (see accessory table).
  - Starter pack of **SCREW1032-50** screws.
- Center section features:
  - Heavy-duty spring-hinge pin for easy installation and removal.
  - Sides that include two (2) vents and a fan grill.
  - Can be installed to swing from left to right or right to left.
- Rear section features:
  - The side of the rear section includes 2.50" and 2.00" knockouts.
  - The top and bottom of the rear section include 3.00", 2.00", 1.38" and 1.12" knockouts.
  - Generous cable management lances are located on the rear section as well as or mounting rails.
  - Mounting points for outlet strips.
  - Heavy-duty keyhole for wall mounting.
  - Large opening in the rear for cable access.
- The front locking door and center section are keyed the same (optional key available).

### Specifications

- 14-gauge welded rear section; 16-gauge center section and doors.
- EIA-compliant adjustable depth mounting rails.
- Grounding lugs are located on top and bottom of the door, center and rear sections.
- UL Listed 2416 load rated for up to 350 lbs (158 kg). Static Load tested to 1,400 lbs (635 kg).
- **NEW: Seismic rated up to 200 lbs (90.72 kg) of dynamic load with an Ip factor of 1.5 in accordance with the IBC 2018, CBC 2019, NBC 2018, ASCE 7-16 and ASCE 7-10.**
- Rugged sand-textured black powder paint reduces the look of fingerprints and marks.
- TAA-compliant for GSA Schedule purchases.
- RoHS Compliant.
- Manufactured in North America within an ISO 9001:2015 certified facility.

### Accessories

- |                                    |   |
|------------------------------------|---|
| • Vertical Cable Tray              | • Rack Panels                           |
| • Horizontal Hinged Cable Manager  | • Horizontal Steel Finger Cable Manager |
| • Horizontal Lacing Strip          | • Universal Rack Shelf                  |
| • Two Post Mounting Clamping Shelf | • Magnet Panel Cover                    |
| • Rack Unit Label                  | • Fan Kits                              |
| • Grounding & Bonding              | • Mounting Hardware                     |
| • PDUs and Outlet Strips           |   |





Part No. Vented Door	Part No. Window Door	Overall Dimensions			Rack Units	Mounting (Usable) Dimensions		
		Height	Width	Depth		Height	Width	Depth
HWM2412U20BK	HWM2412U20WDBK	27.81	24.68	25.67	12U	21.00	19.00	22.85
HWM2412U26BK	HWM2412U26WDBK	27.81	24.68	31.67	12U	21.00	19.00	28.85
HWM2420U20BK	HWM2420U20WDBK	41.81	24.68	25.67	20U	35.00	19.00	22.85
HWM2420U26BK	HWM2420U26WDBK	41.81	24.68	31.67	20U	35.00	19.00	28.85
HWM2424U20BK	HWM2424U20WDBK	48.81	24.68	25.67	24U	42.00	19.00	22.85
HWM2424U26BK	HWM2424U26WDBK	48.81	24.68	31.67	24U	42.00	19.00	28.85
HWM2432U20BK	HWM2432U20WDBK	62.81	24.68	25.67	32U	56.00	19.00	22.85
HWM2432U26BK	HWM2432U26WDBK	62.81	24.68	31.67	32U	56.00	19.00	28.85

Note: Mounting Dimensions / Usable Depth is the maximum equipment depth that will allow the center section of the cabinet to swing out unimpeded.

## Accessories

Cabinet Rack Units	Locking Solid Door *Special Order*	Tapped 10-32 Rail (Pair)	Square Hole Rail (Pair)	Vertical Cable Manager
12U	HWM2412U20WDBK	HWM2412U20WDBK	HWM2412U20WDBK	-
20U	HWM2420U20WDBK	HWM2420U20WDBK	HWM2420U20WDBK	-
24U	HWM2424U20WDBK	HWM2424U20WDBK	HWM2424U20WDBK	VCT42
32U	HWM2432U20WDBK	HWM2432U20WDBK	HWM2432U20WDBK	VCT56

Lock Keyed Differently

Part No.	HWMSLOCK
----------	----------

Tags: **Sectional Wall Mount Rack, Pivoting Rack, Data Wall Cabinet, Dual Hinge, Hinged Swing Gate,** *Data subject to change without notice*  
**Edge Computing**

© 2022. Hammond Manufacturing Ltd. All rights reserved.