

**HSS 3.2-9.5 EL W13M****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

The heat-shrinkable sleeve is printable on 2 sides and can be used for marking and insulating cables and wires. The flexible, heat-shrink material enables a firm, perfect fit around the conductor and therefore saves space.

**General ordering data**

|                    |                                                       |
|--------------------|-------------------------------------------------------|
| Version            | Conductor and cable markers, 3.2 - 9.5 mm, white      |
| Order No.          | <a href="#">1489660000</a>                            |
| Type               | HSS 3.2-9.5 EL W13M                                   |
| GTIN (EAN)         | 4050118299359                                         |
| Qty.               | 1 pièce(s)                                            |
| compatible printer | <a href="#">2599430000</a> <a href="#">2599440000</a> |

## HSS 3.2-9.5 EL W13M

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Caractéristiques techniques

## Dimensions and weights

|            |           |                 |             |
|------------|-----------|-----------------|-------------|
| Depth      | 0,77 mm   | Depth (inches)  | 0,03 inch   |
| Width      | 15,1 mm   | Width (inches)  | 0,594 inch  |
| Length     | 13 000 mm | Length (inches) | 511,81 inch |
| Net weight | 177 g     |                 |             |

## Temperatures

|                             |              |
|-----------------------------|--------------|
| Operating temperature range | -55...135 °C |
|-----------------------------|--------------|

## General data

|                                   |                                                           |                                   |             |
|-----------------------------------|-----------------------------------------------------------|-----------------------------------|-------------|
| Colour                            | white                                                     | Halogen                           | Yes         |
| Length                            | 13 000 mm                                                 | Material                          | Polyolefine |
| Operating temperature range       | -55...135 °C                                              | Operating temperature range, max. | 135 °C      |
| Operating temperature range, min. | -55 °C                                                    | Printed characters                | without     |
| Recommended industries            | Plant manufacture, Energy, Device manufacturer, Machinery | Type of printing                  | neutral     |
| Width                             | 15,1 mm                                                   |                                   |             |

## Conductor and cable markers

|                                   |                   |                                  |                        |
|-----------------------------------|-------------------|----------------------------------|------------------------|
| Conductor O.D.                    | 3.2 - 9.5 mm      | Conductor O.D., max.             | 9,5 mm                 |
| Conductor O.D., min.              | 3,2 mm            | Conductor cross-section, max.    | 16 mm <sup>2</sup>     |
| Conductor cross-section, min.     | 4 mm <sup>2</sup> | Cross-section for connected wire | 4 - 16 mm <sup>2</sup> |
| Halogen                           | Yes               | Rate of shrinkage                | 3:1                    |
| Recommended shrinking temperature | 90 °C             | Text field height                | 14,9 mm                |
| Text field width                  | 0 mm              |                                  |                        |

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC001530    | ETIM 7.0    | EC001530    |
| ETIM 8.0    | EC001530    | ETIM 9.0    | EC001530    |
| ECLASS 9.0  | 27-40-04-01 | ECLASS 9.1  | 27-40-04-01 |
| ECLASS 10.0 | 27-40-04-01 | ECLASS 11.0 | 27-28-11-02 |
| ECLASS 12.0 | 27-28-11-02 | ECLASS 13.0 | 27-28-11-02 |
| ECLASS 14.0 | 27-28-11-02 |             |             |

## Environmental Product Compliance

|                        |                             |
|------------------------|-----------------------------|
| RoHS Compliance Status | Compliant without exemption |
| REACH SVHC             | No SVHC above 0.1 wt%       |

## Approvals

Approvals



|                         |            |
|-------------------------|------------|
| ROHS                    | Conform    |
| UL File Number Search   | UL Website |
| Certificate No. (cURus) | E366310    |

**Fiche de données****HSS 3.2-9.5 EL W13M****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Caractéristiques techniques****Downloads**

Catalogues

[Catalogues in PDF-format](#)

### HSS 3.2-9.5 EL W13M

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Dessins

