



Main

Product	Miniature circuit-breaker
Range	QO
Current Rating	63 A
Voltage Rating	240/415 V AC
Mounting Type	Plug-in
Number of Poles	3P
Circuit Breaker Type	Standard

Complementary

Interrupt Rating	Icu 3 kA 240/415 V AC 50/60 Hz IEC 947-2
Number of Panel Spaces	3
Tightening Torque	44.25 lbf.in (5 N.m) 0.02...0.04 in ² (10...25 mm ²) (AWG 8...AWG 2)
Height	3.15 in (80 mm)
Width	2.24 in (57 mm)
Depth	2.91 in (74 mm)
Net Weight	0.81 lb(US) (0.367 kg)

Environment

Certifications	IEC
Ambient Rating	104 °F (40 °C)

Ordering and shipping details

Category	00920-QO INTERNATIONAL SENA
Discount Schedule	DE2A
GTIN	785901628699
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.40 in (8.636 cm)
Package 1 Width	2.30 in (5.842 cm)
Package 1 Length	4.00 in (10.16 cm)
Package 1 Weight	12.96 oz (367.41 g)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Circularity Profile	No need of specific recycling operations
Halogen content performance	Halogen free product

Contractual warranty

Warranty	18 months
----------	-----------