



### Main

Range of product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCKD
Head type	Rotary head
Product compatibility	XCKM XCKL
Associated body	ZCKLD31 ZCKMD35H29 ZCKL7 ZCKMD39H7 ZCKL8 ZCKL1H7 ZCKM8H7 ZCKM1H7 ZCKM7 ZCKMD37H7 ZCKM9H29 ZCKM5 ZCKMD31 ZCKLD39H7 ZCKL1 ZCKM7H29 ZCKL8H7 ZCKM8 ZCKMD31H29 ZCKL7H7 ZCKLD37 ZCKL6H7 ZCKLD35 ZCKM8H29 ZCKM7H7 ZCKL6 ZCKL5 ZCKLD31H7

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

ZCKM1  
 ZCKLD37H7  
 ZCKMD31H7  
 ZCKM6H7  
 ZCKMD37  
 ZCKL5H7  
 ZCKM6  
 ZCKMD37H29  
 ZCKM9  
 ZCKMD39  
 ZCKMD35H7  
 ZCKMD39H29  
 ZCKMD35  
 ZCKM6H29  
 ZCKLD39  
 ZCKLD35H7  
 ZCKM1H29  
 ZCKM5H29  
 ZCKM5H7

Movement of operating head	Rotary
Type of operator	Roller lever spring return metal ball bearing mounted)
Type of approach	Lateral approach, 2 directions

### Complementary

Switch actuation	By 30° cam
Positive opening	With
Head material	Metal

### Environment

Ambient air temperature for operation	-13...158 °F (-25...70 °C)
Ambient air temperature for storage	-40...158 °F (-40...70 °C)
Environmental characteristic	Standard environment

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	3.46 oz (98 g)
Package 1 Height	1.26 in (3.2 cm)
Package 1 width	2.44 in (6.2 cm)
Package 1 Length	2.95 in (7.5 cm)
Unit Type of Package 2	S02
Number of Units in Package 2	40
Package 2 Weight	9.14 lb(US) (4.145 kg)
Package 2 Height	5.91 in (15 cm)
Package 2 width	11.81 in (30 cm)
Package 2 Length	15.75 in (40 cm)

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

## Contractual warranty

---

Warranty	18 months
----------	-----------

---