

RDM428, Aluminum - Multiple Outlet Connector (RDM Mole)

By Burndy Catalog # RDM428

URD Mole, #4 Str. - 250 kcmil Al or Cu 300 kcmil - 350 kcmil , 600 Volt Rating, 5.81 in L.

Features

- Type RDM-28 MOLE connectors are an economical, insulated, submersible service junction suitable for direct burial or for use in enclosures
- Disconnectable Joints allow additions of new services without disturbing previous installations
- Taping is eliminated, Heat Shrink or Force-Fit Rubber Sleeves insulated each joint, Rubber is used to insulate the MOLE body
- Removable sealing covers are supplied on all outlets but two
- REA Listed Tap Kits, including HYLUG, Hardware and Sleeve are ordered separately

Application

For Aluminum And Copper And Direct Burial Or For Use In Enclosures

General

Catalog Number RDM428
Connector Type Tap

EU RoHS Indicator Contact Manufacturer

Insulation Y
Insulation Type Rubber

Material Aluminum Alloy

Number Of Outlets 4

 Sub Brand
 URD MOLE

 Trade Name
 MOLE™

 Type
 RDM-28

 UPC
 781810180006

 UPC 12 Digit
 7818101800066

5.81 in

Dimensions

Dimension - Length Overall

inch



Conductor Related

Conductor - AL Str Size 4 AWG;3 AWG;2 AWG;1

AWG;1/0 AWG;2/0 AWG;3/0 AWG;4/0 AWG;250 kcmil;266 kcmil;300 kcmil;336 kcmil;350

kcmil

Conductor - AL Str Size Range 4 AWG-350 kcmil

Conductor - Copper Str Size 4 AWG;3 AWG;2 AWG;1

AWG;1/0 ;2/0 AWG;3/0 AWG;4/0 AWG;250 kcmil

Conductor - Copper Str Size 4 AWG-250 kcmil

Range

Certifications And Compliance

Buy American Compliant Contact Manufacturer
Certification - CSA Approved No
Certification - ETL No

Certification - UL Recognized No
Certification - cULus No
Standards - RoHS Compliance CM

Status

UL Listed No

Logistics

Minimum Pack Quantity 1

Product Assets

Catalogs - BURNDY Master Catalog - Section K - Underground Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog

Customer Notices - Prop 65 Notice

Interactive Catalog - BURNDY Full-Line Digital Catalog

Product Cross Section Image(s) -BUR_RDM28_URDMOLE_LineArt Sales Drawings - SD060327-01 A

Specifications - RDM428

