

New improved LED vapourproof fixture that is rugged in design, easy to install and has a high lumen output.



### APPLICATIONS

**Ideal for underground parking garages, industrial plants and agricultural applications.**

<b>Project</b>	
<b>Type</b>	
<b>Date</b>	
<b>Notes</b>	

### SPECIFICATIONS

#### Construction

Housing is made of galvanized sheet metal with aluminum end caps. The LFW-LED has a specular aluminum reflector and a tempered glass lens as standard. Tempered glass lens has high lumen transmittance and stands up to high temperature environments.

#### LED information

The fixture contains a high efficiency LED Strip that delivers a total lumen output of 7082 lumens at an efficacy of approx 121 lumens/watt. LEDs have a colour temperature of 4000K as standard.

#### Mounting

Fixture comes with 2 stainless steel mounting brackets that facilitate easy and quick mounting direct on the wall or ceiling. Wall mount bracket, and pendant mount accessory available (order separately).

#### Electrical

Total system wattage of the unit is 59W. The standard unit has a high efficiency driver that operates at 120 - 277V. 347V is available as an option. Fixture can be through-wired leading to reduced installation time. Daisy chain up to 16 units in a single run.

#### Finish

Fixture has a chemical resistant polyester powder coat grey finish


#### Options

- 0 - 10V dimming
- Junction box assembly (sold separately)

<b>Watts</b>	<b>59W</b>
<b>Equivalent to</b>	<b>&gt;3 lamp T5 fluorescent fixture</b>
<b>Lumens</b>	<b>min. 7,082</b>
<b>Efficacy</b>	<b>121 lumens per watt</b>

<b>Operating Temperature</b>	<b>-40°C to +40°C</b>
<b>Certification</b>	<b>cULus, IP66, DLC</b>
<b>LED Life</b>	<b>100,000 hours</b>
<b>Color Temperature</b>	<b>4000K (standard)</b>
<b>Warranty</b>	<b>5 years</b>
<b>Weight</b>	<b>7 lbs</b>
<b>CRI</b>	<b>&gt;80</b>
<b>Total Harmonic Distortion</b>	<b>18.58%</b>
<b>Power Factor</b>	<b>0.92</b>

### DIMENSIONS




#### Easy installation & maintenance

Fixture is designed for through-wiring leading to reduced installation time. LED array and driver slide in and out for easy maintenance.



ACCESSORIES

(order separately)



Wall Mount bracket



Pendant Mount accessory



Junction Box accessory

ORDERING GUIDE

<b>LFW</b>	-	<b>LED60</b>	-		-		-	
				<b>VOLTAGE</b>		<b>COLOUR TEMP</b>		<b>LENS</b>
				<b>B - 120 - 277V*</b> <b>C - 347V</b>		<b>4K - 4000K*</b>		<b>TG - TEMPERED GLASS*</b>
								<b>OPTIONS</b>
								<b>DIM - 0 - 10V dimming</b>

\* Standard configuration